LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF—:	LOCATED IN—:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY	T. 26 N. S., R. 11 E. W.	K-5; K-7;
2. PROPERTY CONTROLLING IN SECTION 13	T. 26 N. S., R. 11 E. W.	3; 10
3. MISCELLANEOUS PROPERTY IN SECTION ____	T. ____ N. S., R. ____ E. W.	

4. LOT NO. _____, RECORDED PLAT _____

5. PRIVATE CLAIMS _____

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, CARL F. ROSER, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on FEBRUARY 1, 1983, established re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

B. CONTINUED:

10 - ESTAB SW COR OF W 1/2-NW 1/4-SW 1/4 OF SEC 13 EQUIDISTANT & ON LINE BETWEEN THE W 1/4 COR & SW COR OF SEC 13.

C. CONTINUED:

10
DROVE 5/8" X 36" REROD W/RLS CAP & SET CEDAR POST W/LOC TAG

8" MAPLE	N86°E	52.3
8" OAK	N12°W	54.3
2" R. PINE	S16°E	8.7

3
DROVE 5/8" X 36" REROD W/RLS CAP & SET CEDAR POST W/LOC TAG

9" W. PINE	S74°E	89.85
P. POLE	S60°W	44.04
12" APPLE	N85°W	13.15

FD 3/8" PIPE INSIDE 1 1/4" S66°05'E 8.04
FD 1 1/4"PIPE (BURIED) N04°21'E 96.82

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

K-5 FD 1/2" REROD (BURIED 0.3') IN APPROX. CTR OF GRAVEL RD IN CURVE THAT FITS CERT SUR WIT BY BATZER (1981), BY CZUBEK (1975) AND BY GOURDIE-FRASER (1974).

K-7 FD OLD COR FN POST HOLE (FN REMAINS S&E) THAT FITS TWO E.P. WATERMAN B.T.'S DATED JULY, 1909; SUG 12", S49 1/2°E, 22.3'AND HEM. 16", N22°W, 26.5'.

3 - DROVE 5/8" X 36" REROD FOR NW COR OF SW 1/4 OF NW 1/4 OF SEC 13. COR FALLS IN OLD CED POST IN OLD E-W FR REMAINS AND 3'-EAST OF OLD FN COR, FN REMAINS E & N. CTR OF OF POWER LINE (NW-SE) IS SOUTH, 42'±.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

K-5
FD 1/2" X 24" REROD NEAR EAST END OF HORIZONTAL E&W 2" PIPE

* FN POST	S25°W	58.05
* 8" APPLE CLUSTER	NORTH	38.55
* 6" ASPEN	N20°E	37.98
SET CEDAR POST W/LOC TAG	SOUTH	33'

K-7
SET DNR MON & CED POST AT OLD COR FN POST HOLE

*24" MAPLE	S49°E	22.0
13" OAK	S28°W	40.4
4" IRONWOOD	N42°W	26.2
4" MAPLE	N45°E	7.4
*HEM STUMP REMAINS	N22°W	26.5

* = WITS FROM PRIOR CERT. SURVEY- Our Bros & dists. * = E.P.W. 1909 WITS

SIGNED BY Carl F. Roser DATE 06/02/83

SURVEYOR'S MICHIGAN REGISTRATION NO. 12028

STATE OF MICHIGAN CARL F. ROSER LAND SURVEYOR No. 12028 REGISTERED LAND SURVEYOR (SEAL)

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _____ DATE _____
MICHIGAN REGISTERED LAND SURVEYOR (SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

BLAIR TWP.
GRAND TRAVERSE COUNTY

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
REVISED MAY 14, 1975

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET