LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF—:	LOCATED IN—:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY	T. 26 N. ~~S.~~, R. 11 ~~E.~~ W.	I-7; I-6;
2. PROPERTY CONTROLLING IN SECTION 14	T. 26 N. ~~S.~~, R. 11 ~~E.~~ W.	10; 12
3. MISCELLANEOUS PROPERTY IN SECTION	T. N. S., R. E. W.	

4. LOT NO. _____, RECORDED PLAT _____

5. PRIVATE CLAIMS _____

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, CARL F. ROSER, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on FEBRUARY 3, 19 83, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

C. CONTINUED:

~~A. Description of original monument and accessories and/or subsequent restoration~~

10

DROVE 5/8" X 36" REROD W/RLS CAP
10" IRONWOOD N70°E 48.8
12" TWIN MAPLE S78°E 34.1
6" MAPLE S50°E 48.9
SET CEDAR POST
W/LOC TAG EAST 33'
CTR N-S TRAIL RD WEST 3'±

12

DROVE 1" X 18" SOLID IRON ROD
26" MAPLE S65°W 113.70
32" W. PINE N28°E 68.70
12" W. PINE S40°E 64.45
SET CEDAR POST
W/LOC TAG EAST 33'
CTR N-S SAND RD WEST 4'±
CTR TRAIL RD E. Thru PINES SOUTH 9'±

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

I-7 FD 1" SOLID IRON ROD AS RECOVERED BY RLS, J. WILCOX IN 1972. FITS OLD WATERMAN SURVEY. COR IS IN LINE WITH APPROX. CTR OF GRAVEL RD (IN RT ANGLE CURVE) LOOKING WEST & SOUTH.

I-6 RE-SET W 1/4 COR OF SEC 14 FROM 3-WITS (RLS, J. WILCOX 1972); HIS COR HAD BEEN GRADED OR KNOCKED OUT. COR FALLS IN WEST EDGE OF TRAIL RD IN DEEP CUT SECTION.

10 - DROVE 5/8" X 36" REROD FOR SW COR OF NW 1/4 OF SW 1/4 OF SEC 14.

12 - ESTAB. NW COR OF SW 1/4 OF SE 1/4 OF SEC 14 MID-WAY & ON LINE BETWEEN FD CTR OF SEC & FD S 1/4 CORNER.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

I-7

FD 1" SOLID IRON ROD
*14" W. PINE S43°W 39.42
4" W. PINE S70°E 72.9
6" MAPLE S75°W 99.5
SET CEDAR POST
W/LOC TAG EAST 33'

I-6

DROVE 5/8" X 36" REROD W/RLS CAP
*14" BASSWOOD N55°E 39.98
*12" MAPLE N10°W 33.78
* 7" MAPLE S50°E 22.58
SET CEDAR POST
W/LOC TAG EAST 33'

* = J. WILCOX WITS

* = J. WILCOX WITS.

SIGNED BY Carl F. Roser 06/02/83 DATE _____

SURVEYOR'S MICHIGAN REGISTRATION NO. 12028

STATE OF MICHIGAN (SEAL) CARL F. ROSER LAND SURVEYOR No. 12028 REGISTERED LAND SURVEYOR

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _____ DATE _____
MICHIGAN REGISTERED LAND SURVEYOR

(SEAL)

BLAIR TWP.
GRAND TRAVERSE COUNTY

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
REVISED MAY 14, 1975

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET