LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF—:	LOCATED IN—:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY	T. ____ N. S., R. ____ E. W.	
2. PROPERTY CONTROLLING IN SECTION 23	,T. 27 N. S., R. 10 E. W.	14, 5, 12, 8, 11
3. MISCELLANEOUS PROPERTY IN SECTION ____	,T. ____ N. S., R. ____ E. W.	
4. LOT NO. ____ , RECORDED PLAT ____		
5. PRIVATE CLAIMS ____		

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Carl F. Roser, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on April 28, 1981, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on ____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX

C. Continued:

8

Set 5/8" x 36" re-rod w/R.L.S. cap and ced. post w/loc tag.

P. Pole	S40°W	41.54
8" R. Pine	S03°W	59.77
14" W. Pine	N86°E	71.37

11

Fd. round conc. mon. added ced. post w/loc. tag.

*5" W. Pine	N20°W	16.24
*8" Maple	N45°E	8.66

*=Old Wits.

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

14 Estab. 1/8 cor. per standard B.L.M. instructions.
5 Estab. 1/8 cor. per standard B.L.M. instructions.
12 Estab. 1/8 cor. per standard B.L.M. instructions.
8 Estab. 1/8 cor. per standard B.L.M. instructions.
11 Found round conc. monument for ctr. of SW1/4 of S-23.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

14

Set 5/8" x 36" re-rod w/R.L.S. cap & ced. post w/loc. tag

8" Oak	S32°W	13.6
5" Maple	S63°E	4.3
14" R. Pine	North	6.5
Ctr. E-W Tr. Rd.	N.	230'±

5

Set 5/8" x 36" re-rod w/R.L.S. cap & ced. post w/loc. tag

10" Maple	N65°E	30.6
7" Oak	N70°W	9.9
7" Maple	S30°W	13.6

12

Set 5/8" x36" re-rod w/R.L.S. cap & cedar post w/loc. tag.

4" W. Pine	N55°E	14.9
5" W. Pine	S20°W	28.7
5" Maple	S65°W	23.8

SIGNED BY Carl F. Roser 6-05-81 DATE ____

STATE OF MICHIGAN (SEAL) CARL F. ROSER LAND SURVEYOR No. 12028 REGISTERED LAND SURVEYOR

SURVEYOR'S MICHIGAN REGISTRATION NO. 12028

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY ____ DATE ____
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY ____ DATE ____
MICHIGAN REGISTERED LAND SURVEYOR (SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. ____

T27N - R10W
GRAND TRAVERSE COUNTY

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
REVISED MAY 14, 1975

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET