LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF -: LUCATED IN -:	
1. PUBLIC LAND SURVEY T. 28 $\stackrel{N}{\longrightarrow}$, R. 9 $\stackrel{D}{\longleftarrow}$.	
2. PROPERTY CONTROLL- ING IN SECTION——, T. ——— S., R. —— W.	
3. MISCELLANEOUS N. E. PROPERTY IN SECTION T. T. S., R. W.	
4. LOT NO, RECORDED PLAT	
5. PRIVATE CLAIMS	
	FILING NUMBER
I, Carl F. Roser , do hereby certify that un the corner points mentioned in lines 1 and 2 above were, in a field survey re-established, monumented, re-monumented, recovered or restored as expand rules therefore as required in the current manual of survey instruction Bureau of Land Management or by a decree of a court of law. Furthermor and 5 above were, in a field survey on	on December 3, 1977, established, pressed below and in conformance with regulations is of the United States Department of the Interior, e, that the corner points mentioned in lines 3, 4 and, recovered, restored, established or re-established the Board of Registration for Land Surveyors or, by a
A. Description of original monument and accessories and/or subsequent re-	estoration:
	•
B. Description of corner evidence found and/or method applied in restoring Fd. boat spk. for 1/2 corner comm. to Sec. 5 (T28N-	R9W) & Sec. 32 (T29N-R9W) as estab.
	R9W) & Sec. 32 (T29N-R9W) as estab. ine of Sec. 5 in 1937. Corner seems Govt. B.T. which means he accepted (1850) on township line. Corner also . Corner is 3½ South of center of
Fd. boat spk. for 4 corner comm. to Sec. 5 (T28N-by M.S.H.D. (1955) per C. O. Carver survey of N 1 to agree closely with Tuller (1890±) who says fd. 4 corner comm. to Secs. 5 & 32 per U.S. resurvey fits Steele (1894) distance east 4 mile very good	R9W) & Sec. 32 (T29N-R9W) as estab. ine of Sec. 5 in 1937. Corner seems Govt. B.T. which means he accepted (1850) on township line. Corner also. Corner is 3½ South of center of w to N.
Fd. boat spk. for \$\frac{1}{4}\$ corner comm. to Sec. 5 (T28N-by M.S.H.D. (1955) per C. O. Carver survey of N 1 to agree closely with Tuller (1890±) who say's fd. \$\frac{1}{4}\$ corner comm. to Secs. 5 \$\frac{3}{6}\$ 32 per U.S. resurvey fits Steele (1894) distance east \$\frac{1}{2}\$ mile very good E-W b'top road and in line with old fence tree ro C. Description of monument for corner and accessories established to perpose D-1	R9W) & Sec. 32 (T29N-R9W) as estab. ine of Sec. 5 in 1937. Corner seems Govt. B.T. which means he accepted (1850) on township line. Corner also. Corner is 3½ South of center of w to N.
Fd. boat spk. for \$\frac{1}{4}\$ corner comm. to Sec. 5 (T28N-by M.S.H.D. (1955) per C. O. Carver survey of N 1 to agree closely with Tuller (1890±) who say's fd. \$\frac{1}{4}\$ corner comm. to Secs. 5 \$\frac{3}{6}\$ 32 per U.S. resurvey fits Steele (1894) distance east \$\frac{1}{2}\$ mile very good E-W b'top road and in line with old fence tree ro C. Description of monument for corner and accessories established to perp D-1 Fd. boat spk. 3'\$\frac{1}{2}\$ of Ct	R9W) & Sec. 32 (T29N-R9W) as estab. ine of Sec. 5 in 1937. Corner seems Govt. B.T. which means he accepted (1850) on township line. Corner also . Corner is 3½ South of center of w to N. Detuate locating the position of the corner: r. E-W B'top Road
Fd. boat spk. for \$\frac{1}{4}\$ corner comm. to Sec. 5 (T28N-by M.S.H.D. (1955) per C. O. Carver survey of N 1 to agree closely with Tuller (1890±) who say's fd. \$\frac{1}{4}\$ corner comm. to Secs. 5 \$\frac{3}{6}\$ 32 per U.S. resurvey fits Steele (1894) distance east \$\frac{1}{2}\$ mile very good E-W b'top road and in line with old fence tree ro C. Description of monument for corner and accessories established to perp D-1 Fd. boat spk. 3'\$\frac{1}{2}\$ of Ct	R9W) & Sec. 32 (T29N-R9W) as estab. ine of Sec. 5 in 1937. Corner seems Govt. B.T. which means he accepted (1850) on township line. Corner also . Corner is 3½ South of center of w to N. Detuate locating the position of the corner: r. E-W B'top Road
Fd. boat spk. for \$\frac{1}{4}\$ corner comm. to Sec. 5 (T28N-by M.S.H.D. (1955) per C. O. Carver survey of N 1 to agree closely with Tuller (1890±) who say's fd. \$\frac{1}{4}\$ corner comm. to Secs. 5 \$\frac{3}{4}\$ 2 per U.S. resurvey fits Steele (1894) distance east \$\frac{1}{2}\$ mile very good E-W b'top road and in line with old fence tree ro C. Description of monument for corner and accessories established to perport D-1	R9W) & Sec. 32 (T29N-R9W) as estab. ine of Sec. 5 in 1937. Corner seems Govt. B.T. which means he accepted (1850) on township line. Corner also . Corner is 3½ South of center of w to N. Detuate locating the position of the corner: r. E-W B'top Road
Fd. boat spk. for \$\frac{1}{4}\$ corner comm. to Sec. 5 (T28N-by M.S.H.D. (1955) per C. O. Carver survey of N 1 to agree closely with Tuller (1890±) who say's fd. \$\frac{1}{4}\$ corner comm. to Secs. 5 \$\frac{3}{4}\$ 2 per U.S. resurvey fits Steele (1894) distance east \$\frac{1}{2}\$ mile very good E-W b'top road and in line with old fence tree ro C. Description of monument for corner and accessories established to perport D-1 Fd. boat spk. 3'±S of Ct 9" Hemlock S67°E 14" W. Pine N72°E P. Pole N03°E	R9W) & Sec. 32 (T29N-R9W) as estab. ine of Sec. 5 in 1937. Corner seems Govt. B.T. which means he accepted (1850) on township line. Corner also . Corner is 3± South of center of w to N. Detuate locating the position of the corner: r. E-W B'top Road 73.78 161.66 113.40
Fd. boat spk. for \$\frac{1}{4}\$ corner comm. to Sec. 5 (T28N-by M.S.H.D. (1955) per C. O. Carver survey of N 1 to agree closely with Tuller (1890±) who say's fd. \$\frac{1}{4}\$ corner comm. to Secs. 5 \$\frac{3}{4}\$ 2 per U.S. resurvey fits Steele (1894) distance east \$\frac{1}{2}\$ mile very good E-W b'top road and in line with old fence tree ro C. Description of monument for corner and accessories established to perport Fd. boat spk. 3'±S of Ct 9" Hemlock S67°E 14" W. Pine N72°E P. Pole N03°E	R9W) & Sec. 32 (T29N-R9W) as estab. ine of Sec. 5 in 1937. Corner seems Govt. B.T. which means he accepted (1850) on township line. Corner also . Corner is 3± South of center of w to N. Detuate locating the position of the corner: r. E-W B'top Road 73.78 161.66 113.40
Fd. boat spk. for \$\frac{1}{4}\$ corner comm. to Sec. 5 (T28N-by M.S.H.D. (1955) per C. 0. Carver survey of N 1 to agree closely with Tuller (1890±) who says fd. \$\frac{1}{4}\$ corner comm. to Secs. 5 \$\frac{1}{4}\$ 32 per U.S. resurvey fits Steele (1894) distance east \$\frac{1}{4}\$ mile very good E-W b'top road and in line with old fence tree ro C. Description of monument for corner and accessories established to perpose the second s	R9W) & Sec. 32 (T29N-R9W) as estab. ine of Sec. 5 in 1937. Corner seems Govt. B.T. which means he accepted (1850) on township line. Corner also . Corner is 3± South of center of w to N. Detuate locating the position of the corner: T. E-W B'top Road 73.78 161.66 113.40 CARL FROSER LAND
Fd. boat spk. for \$\frac{1}{4}\$ corner comm. to Sec. 5 (T28N-by M.S.H.D. (1955) per C. 0. Carver survey of N 1 to agree closely with Tuller (1890±) who says fd. \$\frac{1}{4}\$ corner comm. to Secs. 5 \$\frac{1}{4}\$ 32 per U.S. resurvey fits Steele (1894) distance east \$\frac{1}{4}\$ mile very good E-W b'top road and in line with old fence tree ro C. Description of monument for corner and accessories established to perpose the second s	R9W) & Sec. 32 (T29N-R9W) as estab. ine of Sec. 5 in 1937. Corner seems Govt. B.T. which means he accepted (1850) on township line. Corner also . Corner is 3± South of center of w to N. Detuate locating the position of the corner: T. E-W B'top Road 73.78 161.66 113.40 CARL FROSER LAND
Fd. boat spk. for \$\frac{1}{4}\$ corner comm. to Sec. 5 (T28N-by M.S.H.D. (1955) per C. 0. Carver survey of N 1 to agree closely with Tuller (1890±) who say's fd. \$\frac{1}{4}\$ corner comm. to Secs. 5 \$\frac{1}{6}\$ 32 per U.S. resurvey fits Steele (1894) distance east \$\frac{1}{2}\$ mile very good E-W b'top road and in line with old fence tree ro C. Description of monument for corner and accessories established to pergonal to the corner and accessories established to pergonal	R9W) & Sec. 32 (T29N-R9W) as estab. ine of Sec. 5 in 1937. Corner seems Govt. B.T. which means he accepted (1850) on township line. Corner also . Corner is 3± South of center of w to N. Detuate locating the position of the corner: T. E-W B'top Road 73.78 161.66 113.40 DATE DATE CARL F. ROSER LAND SURVEYOR No. 12028
Fd. boat spk. for ½ corner comm. to Sec. 5 (T28N-by M.S.H.D. (1955) per C. 0. Carver survey of N 1 to agree closely with Tuller (1890±) who say's fd. ½ corner comm. to Secs. 5 & 32 per U.S. resurvey fits Steele (1894) distance east ½ mile very good E-W b'top road and in line with old fence tree ro C. Description of monument for corner and accessories established to per Pd. boat spk. 3'±S of Ct 9" Hemlock S67°E 14" W. Pine N72°E P. Pole N03°E SIGNED BY A-10-78 SURVEYOR'S MICHIGAN REGISTRATION NO. 12028 FOR STATE AND UNITED STATES AGENCIES: SIGNED BY	R9W) & Sec. 32 (T29N-R9W) as estab. ine of Sec. 5 in 1937. Corner seems Govt. B.T. which means he accepted (1850) on township line. Corner also . Corner is 3± South of center of w to N. Detuate locating the position of the corner: T. E-W B'top Road 73.78 161.66 113.40 DATE DATE CARL F. ROSER LAND SURVEYOR NO. 12028 LAND SURVEYOR NO. 12
Fd. boat spk. for ½ corner comm. to Sec. 5 (T28N-by M.S.H.D. (1955) per C. O. Carver survey of N 1 to agree closely with Tuller (1890±) who say's fd. ½ corner comm. to Secs. 5 & 32 per U.S. resurvey fits Steele (1894) distance east ½ mile very good E-W b'top road and in line with old fence tree ro C. Description of monument for corner and accessories established to per Pd. boat spk. 3'±S of Ct 9" Hemlock S67°E 14" W. Pine N72°E P. Pole N03°E SIGNED BY A-10-78 SURVEYOR'S MICHIGAN REGISTRATION NO. 12028 FOR STATE AND UNITED STATES AGENCIES: SIGNED BY SIGNED BY STATES AGENCIES:	R9W) & Sec. 32 (T29N-R9W) as estab. ine of Sec. 5 in 1937. Corner seems Govt. B.T. which means he accepted (1850) on township line. Corner also . Corner is 3± South of center of w to N. Detuate locating the position of the corner: T. E-W B'top Road 73.78 161.66 113.40 DATE DATE CARL F. ROSER LAND SURVEYOR NO. 12028 LAND SURVEYOR NO. 12
Fd. boat spk. for ½ corner comm. to Sec. 5 (T28N-by M.S.H.D. (1955) per C. O. Carver survey of N 1 to agree closely with Tuller (1890±) who say's fd. ½ corner comm. to Secs. 5 & 32 per U.S. resurvey fits Steele (1894) distance east ½ mile very good E-W b'top road and in line with old fence tree ro C. Description of monument for corner and accessories established to pergonal description of monument for corner and accessories established to pergonal description of monument for corner and accessories established to pergonal description of monument for corner and accessories established to pergonal description of monument for corner and accessories established to pergonal description of monument for corner and accessories established to pergonal description of monument for corner and accessories established to pergonal description of monument for corner and accessories established to pergonal description of monument for corner and accessories established to pergonal description of monument for corner and accessories established to pergonal description of monument for corner and accessories established to pergonal description of monument for corner and accessories established to pergonal description of monument for corner and accessories established to pergonal description of the following description of	R9W) & Sec. 32 (T29N-R9W) as estab. ine of Sec. 5 in 1937. Corner seems Govt. B.T. which means he accepted (1850) on township line. Corner also . Corner is 3± South of center of w to N. Detuate locating the position of the corner: T. E-W B'top Road 73.78 161.66 113.40 DATE DATE CARL F. ROSER LAND SURVEYOR NO. 12028 LAND SURVEYOR NO. 12
Fd. boat spk. for ½ corner comm. to Sec. 5 (T28N-by M.S.H.D. (1955) per C. O. Carver survey of N 1 to agree closely with Tuller (1890±) who say's fd. ½ corner comm. to Secs. 5 & 32 per U.S. resurvey fits Steele (1894) distance east ½ mile very good E-W b'top road and in line with old fence tree ro C. Description of monument for corner and accessories established to per Per Hemlock S67°E 14" W. Pine N72°E P. Pole N03°E SIGNED BY A-10-78 SURVEYOR'S MICHIGAN REGISTRATION NO. 12028 FOR STATE AND UNITED STATES AGENCIES: SIGNED BY	R9W) & Sec. 32 (T29N-R9W) as estab. ine of Sec. 5 in 1937. Corner seems Govt. B.T. which means he accepted (1850) on township line. Corner also . Corner is 3½ South of center of w to N. Detuate locating the position of the corner: T. E-W B'top Road 73.78 161.66 113.40 DATE DATE