LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF—:	LOCATED IN—:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY	T. 28 N. S., R. 9 E. W.	B-3
2. PROPERTY CONTROLLING IN SECTION 6	,T. 28 N. S., R. 9 E. W.	9, 12, 13
3. MISCELLANEOUS PROPERTY IN SECTION	,T. N. S., R. E. W.	

4. LOT NO. _____ , RECORDED PLAT _____

5. PRIVATE CLAIMS _____

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, CARL F. ROSER, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on 2/8, 1982, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

C. CONT. 13

FD 1" PIPE W/RLS CAP #13030 &
SET CED. POST W/LOC TAG.

18" TWIN HEMLOCK	WEST	20.3
5" W. PINE	N15°W	30.0
18" MAPLE	N55°E	24.7

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

B-3 FD 1 1/4" IR ROD, BURIED 12". COR FITS PREVIOUS SURVEYS BY GEO. STEELE (1894), E.P. WATERMAN (1917), M.S.H.D. (1963) AND GOURDIE-FRASER & ASSOC. (1973).

9 FD & ACCEPTED RE-ROD BY RLS, GLEN DELAMATER FOR NE COR OF GOVT LOT 2. FITS 1973 SUR. BY GOURDIE-FRASER & ASSOC.

12 FD OLD 1" PIPE FOR SW COR OF GOVT LOT 2. COR FITS PREVIOUS SURVEY'S BY E.P. WATERMAN (1917), NORTON-KOBBINS (1963), M.S.H.D. (1963) AND GOURDIE-FRASER (1973).

13 FD 1" PIPE FOR SE COR OF GOVT LOT2. COR FITS 1894 SUR. BY GEO. STEELE, 1917 SUR. BY E.P. WATERMAN & 1973 SUR. BY GOURDIE-FRASER & ASSOC.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

B-3
FD OLD 1 1/4" IR ROD. IN PASTURE. NO WIT. AVAIL.

9
FD 5/8" ROD W/RLS CAP #13030 & SET CED. POST W/LOC TAG.

7" MAPLE	S85°E	10.6
11" ASH	S40°W	13.3
4" B CHERRY	N12°W	8.4

12
FD OLD 1" PIPE W/RLS CAP #13030 AND SET CED POST W/LOC TAG.

3" CEDAR	N30°E	15.5
7" CEDAR	S45°W	8.8
14" W PINE	S75°E	25.8

SIGNED BY Carl F. Roser 02-10-82 DATE _____

STATE OF MICHIGAN CARL F. ROSER LAND SURVEYOR No. 12028 (SEAL) REGISTERED LAND SURVEYOR

SURVEYOR'S MICHIGAN REGISTRATION NO. 12028

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _____ DATE _____
MICHIGAN REGISTERED LAND SURVEYOR

(SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

ACME TWP
GD. TRAVERSE CO.

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
REVISED MAY 14, 1975

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET