

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

HOUGHTON COUNTY

FOR CORNERS OF--:	LOCATED IN--:	CORNER CODE NUMBER	
1. PUBLIC LAND SURVEY _____	T. <u>51</u> N. <u>X.</u> R. <u>36</u> <u>X.</u> W.	E-12	F-12
2. PROPERTY CONTROLLING IN SECTION <u>33</u>	T. <u>51</u> N. <u>X.</u> R. <u>36</u> <u>X.</u> W.	5	4
3. MISCELLANEOUS PROPERTY IN SECTION _____	T. _____ N. _____ R. _____ E. _____ W. _____		
4. LOT NO. _____, RECORDED PLAT _____			
5. PRIVATE CLAIMS _____			

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Keith L. Sackett, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on See below, 19____, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

- Corner E-12: Original monument and accessories not found.
- Corner F-12: Not set on original survey nor subsequently apparently.
- Corner 5: Not set on original survey nor subsequently apparently.
- Corner 4: Not set on original survey nor subsequently apparently.

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

- Corner E-12: Restored 5-4-82 on line by proportion between 1/16 corner south and Section corner north.
- Corner F-12: Established 5-5-82 during section subdivision.
- Corner 5: Established 5-5-82 during section subdivision.
- Corner 4: Established 5-5-82 during section subdivision.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

- | | | |
|---|--|---|
| Corner E-12: Set 1" I.D. x 32" I.P. w/
alum. cap.
Salsam N18W 10.0 ft. 1/4S, NBT
Salsam N63E 27.6 ft. 1/4S, NBT
Spruce S65W 30.5 ft. 1/4S, NBT
Corner 4: Set 1" I.D. x 32" I.P. w/
alum. cap.
Sugar N68W 12.2 ft 1/16S, BT
Sugar N32E 22.4 ft 1/16S, BT
Sugar S31E 14.0 ft 1/16S, BT | Corner F-12: Set 1" I.D. x 32" I.P. w/
4" alum. cap
8" Cedar S82E 20.2 ft 1/4S, BT
8" Cedar N41E 24.8 ft 1/4S, BT
7" Cedar N36W 14.1 ft 1/4S, BT | Corner 5: Set 1" I.D. x 32"
I.P. w/4" alum. cap
5" Maple N50W 17.5 ft
1/16S, BT
11" Sugar S35E 22.4 ft
1/16S, BT
16" Maple N51E 16.8 ft
1/16S, BT
14" Maple squared S29W 4 ft |
|---|--|---|

SIGNED BY _____ DATE _____

SURVEYOR'S MICHIGAN REGISTRATION NO. _____ (SEAL)


FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____

APPROVED AND SIGNED BY Keith L. Sackett DATE 5-5-82

MICHIGAN REGISTERED LAND SURVEYOR
Keith L. Sackett
Michigan Department of Natural Resources

SURVEYOR'S MICHIGAN REGISTRATION NO. 19006



FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 26, 1971
REVISED MAY 14, 1975

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET