

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

Houghton Co.

FOR CORNERS OF--	LOCATED IN--	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY _____	T. <u>53N</u> N. S., R. <u>33W</u> E. W.	<u>D12</u>
2. PROPERTY CONTROLLING IN SECTION <u>32</u>	, T. <u>53N</u> N. S., R. <u>33W</u> E. W.	<u>5</u>
3. MISCELLANEOUS PROPERTY IN SECTION _____	, T. _____ N. S., R. _____ E. W.	_____
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Keith L. Sackett, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on March 5, 1979, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

Corner D12: Not set on original survey nor subsequently apparently.

Corner 5: Not set on original survey nor subsequently apparently.

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

Corner D12: Established during section subdivision.

Corner 5: Established during section subdivision.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Corner D12: Set cedar post in swamp.

6" Maple	S64°W	25.9 Ft.	1/4 S, BT
7" Maple	N21°W	12.6 Ft.	1/4 S, BT
7" Tamarack	N88°E	50.7 Ft.	1/4 S, BT

Corner 5: Set cedar post in swamp.

10" Maple	S71°W	8.7 Ft.	1/16 S, BT
8" Tamarack	N18°E	15.4 Ft.	1/16 S, BT
6" Tamarack	S70°E	6.1 Ft.	1/16 S, BT

SIGNED BY _____ DATE _____

SURVEYOR'S MICHIGAN REGISTRATION NO. _____ (SEAL)

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____

APPROVED AND SIGNED BY Keith L. Sackett DATE 2/6/80

CHIEF OF SURVEY PARTY
MICHIGAN REGISTERED LAND SURVEYOR
Keith L. Sackett
Dept. of Natural Resources

SURVEYOR'S MICHIGAN REGISTRATION NO. 19006

