

HILLSDALE COUNTY REMONUMENTATION CORNER

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

<u>)</u>	\. <u>\</u> \	1	voztmü(rd.
Q	Ñ	<u> </u>	DEEDS	

For corners in	· •				\mathcal{Q}_{\perp}	FO.J	: SE	U EDS		
HILLSDALE COUNTY WOODBRIDGE TWP (County)	Located In:	Corne	er Code #			. •				
1. Public Land Survey	T <u>8 S</u> R <u>3 W</u> T R T R	L-5				·				
2. Property Controlling S in Section S 3. Miscellaneous S Property in Sec. S	T R	SURVE EMONUMEI FEB 2 3	MOITATION	Re	gister	of Dee	ds Sta	mp & l	File N	lumbei
4. Lot No, Recorded Plan		SECTIC	M	А	вс	D E	F G	н 1	J	K L
5. Private Claims				2	é——	- 5 ——	-4-	_3_	<u> </u>	1-1
				3 4 5	7	-8-	- 9	_10 -	-11-	12
I, EDWARD W. REED , in a field survey on OCTOBER 24, 1998 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:					19 30	-20	21 - 28		—14- —23- —26-	13
NOTE: Not more than 2 comers, all in the on this certificate.	e same town and	range, may be rec	orded	12	31-	-32	33	_34	35	36
QUARTER CORNER COMMON TO	SECTIONS 12 8	k 13								
A. Description of original monument	and accessories	and/or subseque	nt restoration:							
1825: GOVERNMENT SURVEY - CO 1992: A. RINGENBERG, SURVEYO		SPIKE, AND WI	TNESS							
B. Description of corner evidence fo	und and/or meth	od applied in rest	oring or reestablishi	ng corne	r:					
FOUND RAILROAD SPIKE FITTING	WITNESS OF R	INGENBERG								
C. Description of monument for co	orner and access	ories established	to perpetuate locati	ng the p	osition	of the	corne	er:		
PK NAIL IN POWER POLE NAIL IN 12" MAPLE NW CORNER HOUSE (NOT PORCH FACE OF CONC. ANCHOR POST IN LINE WITH REMAINS OF FENCE	SOUTH	24.00' 43.90' 75.52' 21.60'					or EDWA			
AND IS ACCEPTED AS THE BEST A OF THE POSITION OF THE ORIGIN		DENCE					LAN JURVE NC 339 DLAN	D YOR	TO SOLVER	WANDON CO.

Surveyor's Michigan License No. 33985

EDWARD R. REED

Date NOVEMBER 9.1998