

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF--:	LOCATED IN--:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY <u>36</u>	T. <u>1</u> N. <u>1</u> R. <u>1</u> W.	<u>M-12, M-13</u>
2. PROPERTY CONTROLLING IN SECTION <u>36</u>	T. <u>1</u> N. <u>1</u> R. <u>1</u> W.	<u>M-12, M-13</u>
3. MISCELLANEOUS PROPERTY IN SECTION _____	T. _____ N. _____ R. _____ E. _____ W. _____	_____
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, D. Sio do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above (identified with circles on index code diagram - over) were, in a field survey on June 1974, established, re-established, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on June 1974 found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

M-12 Set $\frac{1}{2}$ mile post
 S62W 51 LINKS 16" White Oak N37W 51 LINKS 18" Elm

M-13 Set post
 S49 $\frac{1}{2}$ W 122 LINKS 24" Red Oak N54W 122 LINKS 24" Elm

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

M-12 Set concrete monument with plastic cap with witness from Polaris Engineering Inc.

M-13 Found 3" dia. Solid Gray mon. set by Bess in 1873. Replaced with 20' dia. Concrete mon. with 2' dia. Brass cap.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

M-12 Set concrete monument with plastic cap.
 S120W 11.28' 9" Ash N62E 17.21' 15" Ash
 S69E 24.70' 30" Black Cherry

M-13 Set 20' dia concrete mon. with 2' dia. Brass cap.
 S87E 52.51' Thornapple North 56.19' 14" Trip's Concrete
 N00 $^{\circ}$ 07'36"E 50.0' concrete mon. 12" dia, 18" high S89 $^{\circ}$ 45'05"W 50.0' concrete mon. 12" dia, 18" high

SIGNED BY _____ DATE _____

SURVEYOR'S MICHIGAN REGISTRATION NO. 12029 (SEAL)

FOR STATE AND UNITED STATES AGENCIES:
 SIGNED BY _____ CHIEF OF SURVEY PARTY DATE _____

APPROVED AND SIGNED BY _____ MICHIGAN REGISTERED LAND SURVEYOR DATE _____ (SEAL)