

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

CORNER REQUIRED

| FOR CORNERS OF--: | LOCATED IN--: | CORNER CODE NUMBER |
|--|---------------|--------------------|
| 1. PUBLIC LAND SURVEY <u>36</u> T. <u>1</u> N. R. <u>1</u> W. | | <u>L-11</u> |
| 2. PROPERTY CONTROLLING IN SECTION <u>36</u> T. <u>1</u> N. R. <u>1</u> W. | | <u>L-11</u> |
| 3. MISCELLANEOUS PROPERTY IN SECTION _____ T. _____ N. S., R. _____ E. W. | | |
| 4. LOT NO. _____, RECORDED PLAT _____ | | |
| 5. PRIVATE CLAIMS _____ | | |

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, D Scott do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above (identified with circles on index code diagram-over) were, in a field survey on SEPT 26 1973, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on SEPT 26 1973, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

FOUND RR. SPIKE IN ROAD INTERSECTION
RECOVERED WITH NAILS BY BIRNIE

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

R.R. SPIKE

| | | |
|------------------|--------------|--------------------------|
| <u>S. 37° E.</u> | <u>57.87</u> | <u>TELEPHONE</u> |
| <u>S. 46° W.</u> | <u>41.8</u> | <u>STREET SIGN POST</u> |
| <u>N. 17° W.</u> | <u>43.1</u> | <u>YIELD SIGN POST</u> |
| <u>N. 58° E.</u> | <u>55.19</u> | <u>10" BITUMEN HINGE</u> |

SIGNED BY _____ DATE _____

SURVEYOR'S MICHIGAN REGISTRATION NO. 12029 (SEAL)

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ CHIEF OF SURVEY PARTY DATE _____

APPROVED AND SIGNED BY _____ MICHIGAN REGISTERED LAND SURVEYOR DATE _____ (SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. _____