SUPLEMA 1 REMOVEMENTOR

SECTION

## LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

Liber

9 Page 344

FOI COMBIS IN INGHAM TOWNSHIP			FILED
INGHAM COUNTY	Located In:	Corner Code #	
Public Land Survey     Property Controlling in Section     Miscellaneous Property in Sec.	T_2N R_1E T R T R T R S T R S T R S T R S T R S T R	A-11	980049406 09/29/1998 10:51:44 REGISTER OF DEEDS Paula Johnson INGHAN COUNTY, NI  Register of Deeds Stamp & File Number
4. Lot No, Recor	ded Plat		ABCDEFGHIJKL
I, Maurice H. Mahleu, in a field survey on July 30, 1998, do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and for that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:			2 - 6 - 5 - 4 - 3 - 2 - 1 - 3 - 2 - 1 - 3 - 2 - 1 - 3 - 2 - 1 - 3 - 3 - 2 - 1 - 3 - 3 - 2 - 1 - 3 - 3 - 3 - 3 - 3 - 3 - 3 - 3 - 3
NOTE: Not more than 2 corn on this certificate.	ərs, all in the same town and r	range, may be recorded	8 —19 —20 —21 —22 —23 —24 — 9 — — — — — — — — — — — — — — — — — —
A. Description of original monument and accessories and/or subsequent restoration:			1
<ol> <li>Original corner set by Joseph Wampler D.S. during February, 1826 at a distance of 33.00 chains. "33.00 Int. the Mer. Set P FW; Ash 12 S 79 E 23; M 4 N 53 E 8 1/2".</li> </ol>			12 -31 - 32 - 33 - 36 - 35 - 36 - 36
Additional marginal note the following witnesses:	es to Joseph Wampler's (N : "Inter @ 32.66" "Willow 3	lo Author named) show S 73 E 27 1/2; Willow 6 N4W 2	5 1/2".
3. Corner referred to in a s	survey by A. Jackson, Co.	Surveyor, June 26, 1843 (V1, P.	.71).
4. Corner referred to in a survey by W. H. Rayner, April 26, 1869.  (Continued On Back)			
B. Description of corner evid	ence found and/or method ap	oplied in restoring or reestablishing	corner:
Kelly Road & ±80' South of Lester thoroughly excavated	fenceline West. Found wi d site in 1980, therefore ex . 345 cap #28414 over Les	18998 encircled by a concrete co iness: Nail & Tag #18998 South cavallon not deemed necessary iter's cap and set two iron monuc	side Power Pole East 23.05', Accepted corner as set by
C. Description of monume	nt for corner and accessories	established to perpetuate locating	the position of the corner:
Found 1/2" rerod in 4" conci Witnessed by: Found Nail a Set Nail & Tag #28414 East Set Nail & Tag #28414 Wes Set Nail & Tag #28414 East	nd Tag #18998 South side side Power Pole N 20° W it side 12" Maple S 30° E 6	' 87.23' 33.97'	5 cap #28414 over.
Signed by Man	in AMah	iii Date_	9-17-98
Surveyor's Michigan License	No. 28414		

MAURICE H.

\* MAHIEU

PROFESSIONAL SURVEYOR
No.
28414

FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 26, 1971
REVISED MAY 14,1975

REVISED JAIL, 1163 REVISED OCT., 1995

P.A. 345 INGHAM COUNTY
PEER APPROVED 8/11/98 VV

## A. (CONTINUED)

- 5. Comer referred to In a survey by G. Edwin States, Co. Surveyor November 25 & 26, 1892 (V3, P.204).
- 6. LCRC recorded in Liber 6, Page 91 by Ronnie M. Lester, P.S. #18998 on August 26, 1980. Lester thoroughly excavated the area and found nothing. Set 4" x 36" concrete monument with 1/2" x 38" rerod & cap #18998 with concrete collar and cover at computed position of corner, ±1.5' East of centerline Kelly Road, ±80.0' South of fenceline West. Measured North to A-10 2621.56'; South to A-12, 2621.56'. Measured North to M-10 Vevay 1392.96'; South to M-11 Vevay 1235.40'.

Paragraph of the Control of the Cont

DEC 1 7 1998

SECTION

Rept No 97035 CRIAR 9.00 NSSR 2.00 Total 11.00