غيرة فالمسلا

SECTION

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

Liber

9 Page 350

980049409 09/29/1998 10:51:49 REGISTER OF DEEDS Paula Johnson INGHAN COUNTY, NI

Register of Deads Stemp & File Number

For corners in INGHAM TOWNSHIP **INGHAM COUNTY** Located In: Corner Code # 1. Public Land Survey T 2N R 1E C-12 2. Property Controlling In Section 3. Miscellaneous Property in Sec.

, Recorded Plat 5. Private Claims

I, Maurice H. Mahleu, in a field survey on July 28, 1998, do hereby state that under requirements of P.A. 74. Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and for that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

- A. Description of original monument and accessories and/or subsequent restoration:
- Original corner set by Joseph Wampler D.S. during February, 1826 at a distance of 40.00 chains. "Set Qu. P fw; WO 18 N 72 W 17; WO 15 N 45 E 12".
- Additional notes to Wampler's (different handwriting) show witness: B Oak 16 N 87 1/4 W 41 3/4.
- 3. Road Commission map describes corner as a plow point with the following witnesses: 24" Oak W 28.2'; 18" Elm SE 30.8'; Concrete Anchor Post E 23.5'.
- An Act 132 survey recorded in Liber 2, Page 1091 on April 29, 1977 by George M. Young PS #17640 "Set 1/2" steel rod w/cap. "Witnesses: #16 Nall in 6" Oak N 30° W 65.00"; #16 Nall in 6" Wild Cherry W 49.08"; #16 Nall in Power Pole N 88° E 44.70'.

(Continued On Back)

10

Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found 1/2" iron ±1.5' East centerline Meridian Road on fencelines East and West. Found Witnesses: Nail and Tag #18998 South side 12" Cherry W 48.73'; P.K. Nail North side Power Pole East 44.75'. Excavated a 2' x 2' x 3' area and found nothing. Area is on top of a hill and appears to have been cut considerably during road construction. All evidence of original corner was obliterated due to road construction. Position of 1/2" iron is best location for an obliterated corner. Replaced 1/2" Iron with 3/4" Iron and P.A. 345 cap #28414 and set a monument box around.

Description of monument for corner and accessories established to perpetuate locating the position of the corner: C.

Found 1/2" iron and replaced with 3/4" iron and aluminum P.A. 345 cap #28414

Found Nail and Tag #18998 South side 12" Cherry W 48.73'

Found P.K. Nail North side Power Pole East 44,75 Nail and Tag #28414 West side 8" Ash N 45° E 49.68"

Nall and Tag #28414 North side 12" Oak N 60° W 46.65"

Date 9/22/28

MAURICE H MAHIEU

PROFESSIONAL

TE OF MICHOLINA

Surveyor's Michigan License No. 28414

FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 26, 1971

REVISED JAN., 1963 REVISED OCT., 1995

P.A. 345 INGHAM COUNTY PEER APPROVED 9/22/98 ML

A. (CONTINUED)

- LCRC recorded in Liber 4, Page 47 by George M. Young PS #17640 on April 29, 1977. "Set 1/2" steel rod on line
 mixture bewreen Southwest and Northwest corners of section." Witnesses same as in #3.
- An Act 132 survey recorded in Liber 2, Page 1133 on May 25, 1977 by Austin C. Williams R.L.S. #21275.
 Monumentation not mentioned, witnesses reference to Liber 4, Page 47 (Same as in #3).
- An Act 132 survey recorded in Liber 5, Page 271 on April 1, 1987 by Ronnle M. Lester PS #18998. Monumentation
 described as 1/2" bar 2' East C.L. road. Witnesses: Nall and Tag in South side 12" Cheny, West 48.85"; Nail and Tag in
 South side 12" Oak NW 65.05"; Centerline phone box NE 43.60"; P.K. Nail in North side Utility Pole E 44.75".
- An Act 132 survey recorded in Liber 5, Page 227 on June 11, 1987 by Ronnle M. Lester PS #18998. Monumentation and witnesses same as in #6.
- 9. An Act 132 survey recorded in Liber 7, Page 1210 on August 12, 1997 by Ronnie M. Lester PS #18998. Monumentation described as 1/2" bar. Witnesses: Set galvanized nall and 1 1/4" brass tag "#18998 Lester" South side 12" Cherry Mag. Az. 275° 48.77; Set galvanized nall and 1 1/4" brass tag "#18998 Lester" South side 14" Red Oak Mag. Az. 315° 65.05"; Found P.K. Nall North side Utility Pole Mag. Az. 93° 44.62"; Set galvanized Nall and 1 1/4" brass tag stamped "#18998 Lester" North side 14" Red Oak Mag. Az. 290° 46.88".

Charles Alberta

DEC 1 7 1998

COTTON

Rept No 97035 CRNR 9.00 MSSR 2.00 Total 11.00