## LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

Liber

P.A. 345 INGHAM COUNTY
PEER APPROVED 1164 94

9 Page

100

For corners in AURELIUS TOWNSHIP, INGHAM COUNTY	Located In:	Corner Code #		FILED 960045038 11/22/1996 13:34:51	
1. Public Land Survey	T <u>2N</u> R <u>2W</u> T R T R T R	B-8		REBISTER OF DEEDS Paula Johnson INGHAM COLINTY, MI	
<ol> <li>Property Controlling in Section</li> <li>Miscellaneous Property in Sec.</li> </ol>	S TR S TR S TR S TR			Register of Deeds Stamp & File Nu	ımber
4. Lot No, Record	ded Plat		1   2	B C D E F G H I J B	L M
I, Maurice H. Mahieu, in a field P.A. 74, Michigan P.A. of 1970, with regulations and rules theref States Department of the Interior that the corner points mentioned Michigan Board of Land Surve- monumented, recovered, found a	survey on October 29, 1996 of the corner points mentioned in ore as required in the current in Bureau of Land Managemen d in lines 3, 4 and 5 above w yors or by a Decree of a C s expressed below:	to hereby state that under re- lines 1 and 2 above were in- nanual of survey instructions t or by a decree of a Court of ere in conformance with the ourt of Law; established, re-	of the United 4	7 - 8 - 9 - 10 - 11 - 15 - 14 - 15 - 14	13
NOTE: Not more than 2 com on this certificate.	ers, all in the same town and	range, may be recorded	8 9 10		
A. Description of original ma	onument and accessories a	nd/or subsequent restora	tion: 11		36
<ol> <li>Corner not set in origin</li> <li>County Surveyor A. Jamaterial noted; witnessed</li> <li>County Surveyor A. Jamaterial</li> </ol>	by: Beech 11 S83 1/2 Do 26 N35 3/4E	11	orner 13		<u> </u>
Beech 11	883 1/2E 23 3 3/4E 41 Book 1, Page 383	vas recorded by Marvin	Fourty PS #18989	a on October 11, 1991. Corner is	s noted
B. Description of corner e	vidence found and/or metho	od applied in restoring or	reestablishing corne	r:	wn for
the first 100 feet North of not the nail or tags. Repl appears not to have ever assumed set by A. Jacks	aced 1/2" rod with 3/4" x been farmed. The location.	24" iron rod with cap st on of the fences, stone	amped PA 345, P s and irons have p	and West. Fence to North is do trees called for in L. Bryan surve S 28414. This terrain is hilly and perpetuated the location of the co	1
C. Description of monumer Set 3/4" x 24" iron rod wi Nail and Tag #28414 Not Nail and Tag #28414 We Nail and Tag #28414 Not Nail and Tag #28414 Not Nail and Tag #28414 We	theast side 36" Twin May st side 18" Maple N5°E 4 th side 18" Maple East 3	ble N20°W 23.27 feet 46.13 feet 5.17 feet 6.32 feet	te locating the position dispersion of the locating the locating the position of the locating the	ion of the comer.	•
Signed by	yui HA	ahi	Date	11-15-96	-
Surveyor's Michigan Lice	ense No. 28414				
	A COLOR	FORM	APPROVED BY MICHIGAN ST	REV	3, 1971 D MAY 14,1 SED JAN, 1 SED OCT., 1

## Part A Continued

5. An Act 132 survey in Liber 7, Pages 279-280 was recorded by Larry Bryan PS #25832 on July 5, 1994. Corner is noted as Found diameter chisel pointed rock, replaced with bar and cap #25832. Set Nail and Tag SW side 34" Maple, due East 34.57' Set Nail and Tag W side 26" Maple N5°E 45.83' Set Nail and Tag W side 18" Wild Cherry, S20°E 31.89'
Distance to B9 = 2642.29'

7.8ECONDER 960045028 17.22/1996 12124:51 FEBISTER OF DEEDS PAULA Johnson TROHAM COUNTY,MI

TIPEL

abed 6

100