DEC 1 6 1996

DEG 1 6 1990					
COMMISSION	LAND CORNEL Filing Require	R RECORDATION CERTIFIC ment of Act 74, Mich. P.A. 1	ATE Liber	9 Page	76
For corners in CITY OF EAST LANSING/MERIDIA INGHAM COUNTY	AN TWP Located In:	Corner Code #		FILED	72
Public Land Survey	T_4N_R_1W TR TR		1	1/22/1996 13:34: EGISTER OF DEED Paula Johnson INCHPM COUNTY, M	5
2. Property Controlling S in Section S 3. Miscellaneous S Property in Sec. S	TR TR TR TR		Register of D	eeds Stamp & F	ile Number
4. Lot No, Recorded Plat 5. Private Claims			1 B C D	E F G H I	J K L M
I, Maurice H. Mahieu, in a field survey of requirements of P.A. 74, Michigan P.A. of 19 conformance with regulations and rules there the United States Department of the Interior and /or that the corner points mentioned in Michigan Board of Land Surveyors or by monumented, re-monumented, recovered, for the surveyors of the conformal control of t	on Oct. 23, 1995 and Oct. 970, the corner points mer refore as required in the cur, Bureau of Land Manager lines 3, 4 and 5 above were a Decree of a Court cound as expressed below:	15, 1996 do hereby certify that under ntioned in lines 1 and 2 above were in irrent manual of survey instructions of ment or by a decree of a Court of Law e in conformance with the rules of the of Law; established, re-established	6 -18 -17	-16 15	14 13
NOTE: Not more that 4 corners, all on this certificate.	in the same town and	I range, may be recorded	8 -19 - 20 -	2122	
A. Description of original monument	and accessories and/o	r subsequent restoration:	10 30 29-	2827-	2625
 Original GLO corner was set by chains West of corner common to post common to 1 and 12, T4N, R. 1/2°E 53 An Act 74 Corner Recordation Ingham County Records by James railroad spike was found in the cer confirmed with plat monuments for 	Musgrove Evans, o Sections 5, 6, 7, 8; 2 2W; Witnessed by: V Certificate was record 5 E. Stephens, PS #1	n February 9, 1827 at 85.71 4 lks. South of V.O. 5, N 47°E 41', Be 6 S75 ded in Liber 3, Page 141, 6053 on June 12, 1974. "A	Abbott Road). The	location of this	spike was 47 and 48."
Witnessed by: Survey tag in the West side of Survey tag in the West side of	9 IUIIII VIIIII - 7777 UT	C 01,01 1001			
Survey tag in the East side of a	q ullity pole, 1405 24	See Part A continue	d on back.		
B. Description of corner evidence found a	and/or method applied in re	estoring or reestablishing corner:	at tautha at	Abbatt Doad	Found one
Found 1" iron bar in monument be of James E. Stephens PS 16053. Revealed reconstruction of Abbot bar confirms the location of the consurveyor accepts the location of the monumentation. Left the 1" rod in	t Road in the past wo brner from plat monul he 1" iron bar as the n place.	ould make excavation for any ments found in the plat of We perpetuation of the location o	evidence of former st Oaks Subdivisior f he corner based o	comer futile. F	2. This
C. Description of monument for corner a	nd accessories established	d to perpetuate locating the position	of the corner:		
1" iron bar in monument box, witr Nail & tag #16053, west side utilit Nail & tag #16053, south side utilit Nail & tag #16053, south side 24' PK nail, northeast side 24" Maple Nail & tag #16053, Northwest side	y pole 565 E 67.30 i ity pole N50°E 41.27 'Maple N40°W 56.94 N40°W 57.75 feet	feet	as)		
Signed by Aurus X Surveyor's Michigan License No.	1 Stal		11-96		
SANE OF MICHIGAN	A.	FOR	M APPROVED BY MICHIGAN STA	TE BOARD OF LAND SUR	VEYORS, JAN. 28, 187 REVISED MAY 14,187 REVISED JAN., 198

MAURICE H. MAHIEU SURVEYOR NO.

P.A. 345 INGHAM COUNTY PEER APPROVED_10/31/96 M

> a bede Liber 77

Part A Continued

A-3. An Act 132 survey was recorded in Liber 2, Page 118, on Oct 23, 1974 by James E. Stephens, PS 16053 which shows the corner. Reference is to the Act 74 Certificate in Liber 3, Page 141 (A-2). No other information given.

A-4. An Act 132 survey was recorded in Liber 2, Page 973, on Feb. 7, 1977 by James E. Stephens, PS 16053 which shows the corner as a railroad spike, witnessed by:

Survey tag nailed to W. Side of a utility pole N54°47'E 39.11 feet Survey tag nailed to W. Side of a utility pole S73°34'E 67.37 feet Survey tag nailed to E. Side of a utility pole N65°24'W 31.40 feet

A-5 An Act 288 Subdivision Whitehills Center was recorded in Liber 33 of plats, page 24 & 25, on Sept. 18, 1975, by James E. Stephens, PS 16053 which shows the corner but does not have any other information.

A-6 Ingham County Road Commission Grid Maps (Old) shows a 1" Iron Pipe in Conc.; witnessed by: 4" Cherry SE 35.0' 12"Oak NW 29.6" 6" Maple SW 51.2" 14" Oak NW 78.3' 8" Tw. Maple SE 55.4"

A-7 Ingham County Road Commission Grid Maps (1972) shows the same information as A-6, above.

Part C Continued

Nail & tag #28414, southeast side utility pole S47°W 36.06 feet Nail & tag #28414, nontheast side 14" Maple N50°W 57.81 feet Nail & tag #28414, southeast side utility pole N52°E 41.55 feet Nail & tag #28414, southwest side utility pole S79°E 67.94 feet M-3, T4N, R2W, North 14.31 feet

EBISTER OF DEEDS Paula Johnson INGHAM COUNTY, MI

FIDEL

∂ ₹.586