DEC 2 0 2000

LAND CORNER RECORDATION CERTIFICATE

SECTION

Filing Requirement of Act 74, Mich. P.A. 1970

For corners in IONIA (County)	Located in:	Corner Code #	######################################		LIBE	_R 4	P	AGE 18	4
Public Land Survey 2. Property Controlling S in Section S	T5_N			2	STATE OF MICHIGAN IONIA COUNTY RECEIVED FOR RECORD 22 NOV 2000 2:16:28 PM DIANE M. ADAMS REGISTER OF DEEDS				
3. Miscellaneous S Property in Sec. S	T R		Re	gister c	of Deeds S	Stamp (& File I	Numbe)r
4. Lot No, Recorded Plat				1 A	B C D	E F	G H	ijΚ	LN
·				. 2	6 5	.4	3	2	1
I. MARINUS MULDER do hereby certify that under requirer lines 1 and 2 above were in conf	ments of P.A. 74. Mic	higan P.A. of 1970 the	corner points mentioned in		7 8	9	10	11	12
current manual of survey instruction Management or by a decree of a Cor	s of the United Stat urt of Law and/or that	tes Department of the	Interior, Bureau of Land	i i	18 17	16	15	14	13
above were in conformance with the Court of Law; established, re-expressed below:	e rules of the Michia	an Board of Land Sun	evors or by a Decree of a	7 8	19 20	21	22	23	24
NOTE: Not more than 4 corners, all is on this certificate.	n the same town and i	range, may be recorded		T 1	30 29	28	27	26	25
A. Description of original monument and a	reconnection and/or cubes	rusant raginaration.		12 3	31 32	33	34	35	36
CORNER M-9, T5N-R6W. LUCIUS LYON CORNER M-11, T5N-R6W. PERPETUATION AND OR ESTABLISHMI 11, 1895, RECORDED IN VOLUME 2, PA SURVEYORS COPY OF THE G.L.O. NOTE WILLOW S 60 1/2° E 43 LINKS (28.38 F MONUMENTATION.	ENT: D.C. CRAWFORD IGE 320 OF IONIA COU S ON PAGE 8, CRAWI) FORMER IONIA COUNTY UNTY SURVEYORS RECO FORD HAS MARGINAL W	' SURVEYOR PERFORMED A RDS. CRAWFORD SHOWS 1 TNESS NOTES FOR A-10: 1	SURVEY HAT HE 0" APPLI	OF SECTION FOUND THE EN 30° W 1	N 30, T5 Corne 07 1/2 L	5N-R5W R. IN TI INKS (7)	APRIL 1 1e coui 0.95); 6'	O AND NTY
THE IONIA COUNTY ROAD COMMISSIO WITNESS INDEX SHEETS AS FOLLOWS POLE N.W. 51.35 FEET; STEEL FENCE P	: 1" i ron bar 10.95 i	FEET SOUTH OF THE STA	N 1963. THE ROAD COMMI INDARD CORNER M-10 T5N	SSION H R6W. T	AS WITNES: ELEPHONE	SES FOR Pole n.i	I A-10 0 E. 33.10	N THE Feet; P	OWER
B. Description of corner evidence found an AT A DISTANCE OF 1111.10 FEET SOU TO A DEPTH OF 28" AND FOUND A 6" I	TH OF THE STANDAR	D CORNER M-10, T5N-R	SW, FOUND A 1" STEEL BAF				IRFACE.	EXCAV	ATED
C. Description of monument for corner and REPLACED EXISTING MONUMENTATION WITNESSED BY:	l accessories established IN WITH A 7/8"x24" S	to perpetuate locating the p STEEL ROD WITH A 4" DI	osition of the corner: AMETER ALUMINUM CAP S	TAMPED	- "IONIA CO	UNTY -	P.S. 258	863″	
NAIL & TAG SOUTHEAST SIDE 36" POP NAIL & TAG SOUTH SIDE POWER POLE MOST SOUTH SOUTHEAST CORNER OF NAIL & TAG SOUTH SIDE 4" X 6" GUAR EAST 1/4 CORNER SECTION, 25, 7/8" S	NORTH 58° WEST 49 HOUSE FOUNDATION POST NORTH 61° I).37 FEET N North 33° West 147 East 44.96 Feet		FEET			٠		
Signed by Marus C	. Midde	? Dat	11-8-0	jo o					•
Surveyor's Michigan License No. 2586	63		FORM APPROVED BY MICHIGAN ST	ATE BOARD OF	LAND SURVEYORS, JA	N. 28, 1971			
	ARIBINATE C	MICHIGANIA		Ratific	ed by F		er on word	REVISED M REVISED ROCESSING M	AY 14, 1975 : JAN, 1983 ARCH, 1893

MARINUS A.

MULDER
PROFESSIONAL
NO.
25863
POFESSIONAL
MARINUS A.

MULDER
PROFESSIONAL
NO.
25863

Ratified by Peer Group P.A. 345 Ionia County

Date 8-24-2000 Marinus A. Mulder, Chairman