LAND CORNER RECORDATION CERTIFICATE

K.

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

		CORNER CODE	NUMBER	
1. PUBLIC LAND SURVEY 18 T. 5 $\stackrel{\text{N.}}{\bullet}$, R.	5 w.	B-5, A-5		
2. PROPERTY CONTROLL- N. S., R N. S., R	E. W.			
3. MISCELLANEOUS N. PROPERTY IN SECTION, T S., R	I			
4. LOT NO, RECORDED PLAT				
5. PRIVATE CLAIMS				REGISTER OF DEEDS STAMP AND
				FILING NUMBER
I, Russell Roon, do he the corner points mentioned in lines 1 and 2 above we re-established, monumented, re-monumented, recovere and rules therefore as required in the current manual Bureau of Land Management or by a decree of a cour and 5 above were, in a field survey on as expressed below and in conformance with the rules Decree of a Court of law:	ere, in a fed or rest of survey t of law.	ield survey on tored as expressed instructions of th Furthermore, that 19, found, rec	Novemb below and the United S the corner covered, rest	er, 19 78, established in conformance with regulation tates Department of the Interior points mentioned in lines 3, cored, established or re-established
A. Description of original monument and accessories	and/or si	ibsequent restoratio	on:	
B. Description of corner evidence found and/or meth				
B. Description of corner evidence found and/or meth B-5 Found 1/2 re-rod placed cap D.L.B. 18655.				g corner: with cap #C.P.21265.
B-5 Found 1/2 re-rod placed	A-5	Found 1/2"	re-rod w	rith cap #C.P.21265.
B-5 Found 1/2 re-rod placed cap D.L.B. 18655. C. Description of monument for corner and accessoric R-5, 1/2 Rod	A-5 es establis A-5	Found 1/2" shed to perpetuate Re-rod with c	re-rod w locating the	position of the corner:
B-5 Found 1/2 re-rod placed cap D.L.B. 18655. C. Description of monument for corner and accessoric R-5, 1/2 Rod	A-5 es establis A-5	Found 1/2" shed to perpetuate Re-rod with c	re-rod w locating the	position of the corner:
B-5 Found 1/2 re-rod placed cap D.L.B. 18655. C. Description of monument for corner and accessorie	A-5 es establis A-5	Found 1/2" shed to perpetuate Re-rod with c	locating the cap. I.E. Corn 1.E. Power 1.8' Power	e position of the corner:
B-5 Found 1/2 re-rod placed cap D.L.B. 18655. C. Description of monument for corner and accessorie B-5 1/2 Rod N 63° W, 66.42' 24" Maple N 23° W, 32.55' 17" Maple N 65° E, 40.27' 12" Hickory North 28.75' Fence Cor.	A-5 es establis A-5	Found 1/2" Shed to perpetuate Re-rod with conth 7.49' North 7.49	locating the cap. I.E. Corn 15' Powe 18' Powe 18' Face 28' Powe	e position of the corner: ter 13 er Pole er Pole e of R/W Marker er Pole
B-5 Found 1/2 re-rod placed cap D.L.B. 18655. C. Description of monument for corner and accessoric B-5 1/2 Rod N 63° W, 66.42' 24" Maple N 23° W, 32.55' 17" Maple N 65° E, 40.27' 12" Hickory North 28.75' Fence Cor. S 67° E, 98.73' 18" Walnut	A-5 es establis A-5	Found 1/2" shed to perpetuate Re-rod with conth 7.49' North 7.49	locating the cap. I.E. Corn 15' Powe 18' Powe 18' Face 28' Powe	e position of the corner: ter 13 er Pole er Pole e of R/W Marker er Pole
B-5 Found 1/2 re-rod placed cap D.L.B. 18655. C. Description of monument for corner and accessoric B-5 1/2 Rod N 63° W, 66.42' 24" Maple N 23° W, 32.55' 17" Maple N 65° E, 40.27' 12" Hickory North 28.75' Fence Cor. S 67° E, 98.73' 18" Walnut SIGNED BY	A-5 es establis A-5	Found 1/2" shed to perpetuate Re-rod with conth 7.49' North 7.49	locating the cap. I.E. Corn 15' Powe 18' Powe 18' Face 28' Powe	position of the corner: ner 13 er Pole er Pole e of R/W Marker er Pole er Pole
B-5 Found 1/2 re-rod placed cap D.L.B. 18655. C. Description of monument for corner and accessoric B-5 1/2 Rod N 63° W, 66.42' 24" Maple N 23° W, 32.55' 17" Maple N 65° E, 40.27' 12" Hickory North 28.75' Fence Cor. S 67° E, 98.73' 18" Walnut SIGNED BY	A-5 es establis A-5	Found 1/2" shed to perpetuate Re-rod with conth 7.49' North 7.49	locating the cap. I.E. Corn 1.E. Powe 1.E. Powe 1.E. Powe 1.E. TE	position of the corner: ner 13 er Pole er Pole e of R/W Marker er Pole er Pole
B-5 Found 1/2 re-rod placed cap D.L.B. 18655. C. Description of monument for corner and accessoric B-5 1/2 Rod N 63° W, 66.42' 24" Maple N 23° W, 32.55' 17" Maple N 65° E, 40.27' 12" Hickory North 28.75' Fence Cor. S 67° E, 98.73' 18" Walnut SIGNED BY	A-5 es establis A-5	Found 1/2" Shed to perpetuate Re-rod with conth 7.49' North 7.49	locating the cap. I.E. Corn 1.E. Powe 1.E. Powe 1.E. Powe 1.E. TE	position of the corner: ner 13 er Pole er Pole e of R/W Marker er Pole er Pole er Pole er Pole