## LAND CORNER RECORDATION CERTIFICATE

. (1941년 12 19 200년) 	Filing Requirement of Act 74, Mi	ch. P.A. 1970	LIRER 4	PAGE 126	5		
For corners in Located In:	Corner Code #				COUNTY		
1. Public Land Survey		-		RECEIVED  23 NOV 99			
T		Reg	ister of D	DIANE N REGISTER eeds Stamp	. ADAMS OF DEED & File N	S  umber	
4. Lot No, Recorded Plat		_	1 A B	CDEF	G Н I	J K	L N
5. Private claims		_	2 6	5 4	3	2	1
t, MARINUS MULDER , in a field	survey on JUNE 11	1999 .	4 7	8 9	10	11	12
do hereby certify that under requirements of P.A. 7- lines 1 and 2 above were in conformance with current manual of survey instructions of the United Management or by a decree of a Court of Law and	regulations and rules therefore a 3 States Department of the Interior	s required in the r. Bureau of Land	6 18	17 16	15	14	13
above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree Court of Law; established, re-established, monumented, re-monumented, recovered, found expressed below:			8 19	20 21	22	23	24
NOTE: Not more than 4 corners, all in the same town on this certificate.	n and range, may be recorded		10 30	29 28	27	26	25
A. Description of original monument and accessories and/or	subsequent restoration:	OF TO AUCUST 7	12 31 13	32 33	34	<b>3</b> 5	36
THIS CORNER WAS FIRST ESTABLISHED BY U.S DEPU 1831. A WOOD POST WAS SET WITNESSED BY A: 15			INKS.				
SMITH CALLS FOR A STONE WITNESSED BY A 16" SURVEY OF SECTION 22 T5N-R8W OCTOBER 25-27, 1 CALLED FOR A 14" MAPLE N 47° W 58 3/4 LINKS, AN IONIA COUNTY SURVEYORS COPY OF THE G.L.O. NOT ACCORDING TO HIS SURVEY IN OCTOBER OF 1888.  THE IONIA COUNTY ROAD COMMISSION IMPROVED METERS A 1" IRON IS CALLED FOR WITNESSED BY A: TELEPHOSEN. 46.00 FEET.  THE FORMER STATE HIGHWAY DEPARTMENT IMPROPROFESSIONAL SURVEYOR BRIAN REYNOLDS NO. 316 FOUND A 5/8" IRON IN A MONUMENT BOX WITNESSER ROAD SIGN EAST 18.48 FEET; TOP CENTER U.S.G.S. 10	888 RECORDED IN VOLUME 1, PAGE 4 D A 12" MAPLE S 43 1/2° W 40 LINKS ES. ON PAGE 488 IT STATES HE FOUL  MASH HIGHWAY CIRCA 1949. NO SPECE  SSES FOR H-9 FOUND IN THE SECTION ONE POLE S.E. 72.40 FEET; GUY POLE IN  VED THIS SECTION OF NASH HIGHWA  602 RECORDED H-9 MARCH 26, 1988 ED BY: NAIL & TAG TWIN 6" CHERRY I	54 OF THE IONIA CO FOR WITNESS OBJE ND THE OLD CORNER CIFIC INFORMATION CORNER INDEX SHE V.E. 53.60 FEET; 11" Y AND INCLUDED IT.	UNTY SURV CTS. CRAV BY SMITH COULD BE F ETS. WALNUT N AS PART OF	YEYORS RECOR WFORD HAS A AND WITNESS TOUND ON THE  W. 42.70 FEE HIGHWAY M- F ACT 74 RECO	DS. CRAV MARGINAI ED THE CO  ROAD PLA  T; STEEL F  50.  RDS. REY	VFORD L NOTE IN DRNER  ANS FOR I ENCE POS	I ТНЕ Н-9. ST
B. Description of corner evidence found and/or method app AT THE INTERSECTION OF NASH HIGHWAY AND M-5 AND EXCAVATED TO A DEPTH OF 44" BUT FOUND NO	O FOUND A MONUMENT BOX. INSIDE O OTHER EVIDENCE.		" ROD WITI	1 A 2" BRASS (	CAP. REM	OVED IRO	ıN
C. Description of monument for corner and accessories est SET A 7/8" x 30" STEEL ROD WITH A 4" DIAMETER C MONUMENT - P.S. 25863" REPLACED MONUMENT BE CENTERLINE EASTERLY 4" STEEL POST N 34° W 58. N&T POWER POLE S 3° E 122.5 N&T SOUTH SIDE 14" ASH N 80° E 38.4 N&T S.E. SIDE 14" CHERRY N 50° E 36.4	AP IN PLACE OF THE EXISTING MONU OX, AND WITNESSED CORNER AS FOI .15 FEET 54 FEET 44 FEET	MENTATION. THE 4'		'AMPED "IONI <i>A</i>	COUNTY	SURVEY	
Signed by Marv L 68n	Date	//-3-	· · · · ·	D CHRISTOPP 1441 28 22	. <u> </u>		
Ratified by Peer Group P.A. 345 Ionia County  Date September 9,1999 Marinus A. Mulder, Chairman	MARINUS A.  MULDER PROFUS SHONAL SUNVEYOR No. 25863	FORM APPROVED BY NICHIGAN S	ATE EOARD OF LAN		RPIED FOR WORD	REVISED MA REVISED J Processimo mai	