LIBER 4 PAGE 127

# LAND CORNER RECORDATION CERTIFICATE

**Filing Requirement of Act 74, Mich. P.A. 1970**

For corners in IONIA (County) Located In: Corner Code #

STATE OF MICHIGAN
IONIA COUNTY
RECEIVED FOR RECORD

23 NOV 99 3:14 P.M.

DIANE M. ADAMS
REGISTER OF DEEDS

Register of Deeds Stamp & File Number

1. Public Land Survey T5 N R8 W H-11
   T____ R____
   T____ R____
   T____ R____
2. Property Controlling S____ T____ R____
   in Section S____ T____ R____
3. Miscellaneous S____ T____ R____
   Property in Sec. S____ T____ R____
4. Lot No. _____ , Recorded Plat _____
5. Private Claims _____

| | A | B | C | D | E | F | G | H | I | J | K | L | M |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 1 | | | | | | | | | | | | | |
| 2 | | 6 | 5 | 4 | 3 | 2 | 1 | | | | | | |
| 3 | | | | | | | | | | | | | |
| 4 | | 7 | 8 | 9 | 10 | 11 | 12 | | | | | | |
| 5 | | | | | | | | | | | | | |
| 6 | | 18 | 17 | 16 | 15 | 14 | 13 | | | | | | |
| 7 | | | | | | | | | | | | | |
| 8 | | 19 | 20 | 21 | 22 | 23 | 24 | | | | | | |
| 9 | | | | | | | | | | | | | |
| 10 | | 30 | 29 | 28 | 27 | 26 | 25 | | | | | | |
| 11 | | | | | | | | | | | | | |
| 12 | | 31 | 32 | 33 | 34 | 35 | 36 | | | | | | |
| 13 | | | | | | | | | | | | | |

I, MARINUS MULDER, in a field survey on JUNE 11 1999, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

**NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.**

A. Description of original monument and accessories and/or subsequent restoration:
THIS CORNER WAS FIRST ESTABLISHED BY U.S. DEPUTY SURVEYOR JOHN MULLETT APRIL 25, TO AUGUST 7, 1831. A WOOD POST WAS SET WITNESSED BY A 9" BEECH N 89° W 16 LINKS, AND A 6" BEECH N 89° E 15 LINKS.

PERPETUATION: A.C. SMITH FORMER IONIA COUNTY SURVEYOR PERFORMED A SECTIONAL SURVEY OF SECTION 27, IN JUNE OF 1876. FOR THE PURPOSE OF ESTABLISHING A ROAD ON THE NORTH-SOUTH 1/4 LINE. THIS INFORMATION IS FOUND IN VOLUME 1, PAGE 178 OF THE IONIA COUNTY SURVEYORS RECORDS. SMITH CALLS FOR A STONE AND HAS A WITNESS TO H-11: 30" SUGAR MAPLE N 39° W 96 LINKS.

THE IONIA COUNTY ROAD COMMISSION IMPROVED NASH HIGHWAY CIRCA 1949. NO SPECIFIC INFORMATION COULD BE FOUND ON THE ROAD PLANS FOR H-11.

THE IONIA COUNTY ROAD COMMISSION HAS WITNESSES FOR H-11 FOUND IN THE SECTION CORNER INDEX SHEETS. IT CALLS FOR A 1" IRON WITNESSED BY: TELEPHONE POLE S.E. 72.40 FEET; GUY POLE N.E. 53.60 FEET; 11" WALNUT N.W. 42.70 FEET; STEEL FENCE POST S.W. 46.00 FEET.

THE FORMER STATE HIGHWAY DEPARTMENT IMPROVED THIS SECTION OF NASH HIGHWAY AND INCLUDED IT AS PART OF HIGHWAY M-50.

REGISTERED LAND SURVEYOR WILLIAM HUME ROGERS # 6197 RECORDED H-11 MAY 31, 1972 IN IONIA COUNTY ACT 74 RECORDS FOUND IN LIBER 1, PAGE 67. ROGERS DID NOT SAY WHAT WAS FOUND OR SET BUT HAD THE FOLLOWING WITNESSES: TELEPHONE POLE S.E. 72.40 FEET; STEEL FENCE POST S.W. 46.00 FEET; ROAD MARKER SIGN N 45° E 51.65 FEET; GUY POLE N.E. 53.60 FEET.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:
AT THE INTERSECTION OF NASH HIGHWAY AND TUPPER LAKE ROAD (M-50) FOUND A NAIL & WASHER ON THE PAVED SURFACE. EXCAVATED BELOW AND FOUND A 3/4" x 10" BOAT SPIKE AT A DEPTH OF 8". BELOW THE BOAT SPIKE FOUND A 1" x 24" PIPE. NO FURTHER EVIDENCE WAS FOUND.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:
REPLACED THE EXISTING MONUMENTATION WITH A 7/8" x 24" STEEL ROD WITH A 4" DIAMETER CAP STAMPED "IONIA COUNTY SURVEY MONUMENT - P.S. 25863" SET IN A MONUMENT BOX, WITNESSED BY:

N&T N.E. SIDE POWER POLE S 40° E 73.65 FEET
N&T N.W. SIDE 4" ASH S 43° W 48.52 FEET
N&T S. SIDE 12" ELM CLUMP S 56° W 46.85 FEET
S. EDGE STOP SIGN LEG N 65° E 42.20 FEET

Signed by Marinus A. Mulder Date 11-3-99

Surveyor's Michigan License No. 25863

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 29, 1971
REVISED MAY 14, 1975
REVISED JAN., 1983
ADAPTED FOR WORD PROCESSING MARCH, 1993

Ratified by Peer Group
P.A. 345 Ionia County

Date September 9, 1999
Marinus A. Mulder, Chairman

STATE OF MICHIGAN
MARINUS A. MULDER
PROFESSIONAL SURVEYOR
No. 25863
LICENSED PROFESSIONAL SURVEYOR