SURVEY & REMONUMENTATION

JAN 2 0 1999

LAND CORNER RECORDATION CERTIFICATE

SECTION

Filing Requirement of Act 74, Mich. P.A. 1970

			i iiiig neqe	mement of Act 14, ii	(IGH. 1 .A. 1070	TRES	4	PAGE É	14				
For corners in IONIA		Located In:	Corner	Code #		landa di bar 1	\ 1	t filodo as	29 4				
(County)										CHIGAN			
1. Public Land Survey		T6 <u>N</u> R5_		A-10					CMIA CO CUED FI	DUATY Dr Fred	PTI		
		T R	······································		_	25 NOV 98 2:58 P.M.							
2. Property Controlling	g S	T R R									ill s		
in Section 3. Miscellaneous Property in Sec.	o o	T R T R T R			Reg	gister	r of D	iiji eeds Ş	tamp (AD:WS Filet	lumbe	r	
						, A	. В	C D	E F (∋ H I	J K	LN	
5. Private Claims						2	6	5	4	3	2	1	
. AAADINIIC MI	III DED	in a field a	nimen an	HIME 22 1		3 -	7	8	9	10	11	12	
do hereby certify t	hat under requirer	ments of P.A. 74	Michigan P.	JUNE 23 1 A. of 1970, the corne	r points mentioned in as required in the			l °	,	- 10	1 ;	12	
current manual of	survey instruction	s of the United	States Dep	artment of the Inter	ior, Bureau of Land d in lines 3, 4 and 5	6	18	17	16	15	14	13	
above were in cor Court of Law;	nformance with the	e rules of the M	ichigan Boa	rd of Land Surveyors	s or by a Decree of a covered, found as	8	19	20	21	22	23	24	
expressed below:	Abou formon all i			sy ha voagudod		9 10 ¶	30	29	28	27	26	25	
NOTE: Not more on this ce	than 4 corners, all i ertificate.	u tue same town	ano ranye, m	ry de recurded		11 12	31	32	33	34	35	36	
A. Description of or				toration: URVEYORS. THE U.S.	DEDITTY CHOVEVOR	13	31	JZ	1 33	54		00	
SURVEYOR LUCIUS THE STANDARD CO D.C. CRAWFORD FO APPROXIMATELY 2	LYON IN 1827 AT 1 Drner (M-11, T6N-1 Drmer Ionia Coun 4" Long For His M	THE SOUTHWEST R6W). ITY SURVEYOR R MONUMENTATIO	CORNER OF EMONUMEN' N. IN THE CO	SECTION 30 T6N-R51	SED AT THE STANDAF N (A-11) INTERSECTED ISHIP IN 1890. CRAW OPY OF THE G.L.O. NO E 89 LINKS.) THE Ford	RANG! USED	LINE 6 2 1/4" S	LINKS (: OLID GL	3.96 FEE Azed Ti	T) NOR		
THE IONIA COUNTY	ROAD COMMISSIO	ON IMPROVED AN	ID PAVED KE	EFER HIGHWAY IN 19	63. NO INFORMATION	WAS	FOUNI) FOR A	-10 ON 7	THE ROA	D PLAN	IS.	
THE ROAD COMMIS PORCH N.W. 90.92	SSION HAS WITNES FEET; CORNER FEN	SSES TO A-10 IN ICE POST N.E. 38	THE WITNES: 8.80 FEET; 30	S INDEX SHEETS AS F " MAPLE S.W. 59.42 I	OLLOWS: (1956) 3/4" FEET; CENTER SOUTH	BOAT END (SPIKE OF CUL	WITNES VERT S.I	SED BY E. 41.00	: S.E. C FEET	ORNER 1	HOUSE	
AT THE INTERSECT	TION OF KEEFER HIS CAVATED THE ROA	GHWAY AND ION D BED TO A DEP	IA ROAD ONL		ESS OBJECT REMAINS FOUND. ESTABLISHE								
SET A 7/8" X 36" S SOUTHEA NAIL & T NORTHEA COMMIS	TEEL ROD WITH A AST CORNER OF LO AG NORTH SIDE 34 AST CORNER OF LO SION.) LINE OF ROAD SIGN	4" DIAMETER CA OWER CONCRETE B" MAPLE S 76° OWER CONCRETE I POST N 53° E 3	AP STAMPED STEP TO HO W 87.25 FE STEP OF HO 34.98 FEET	USE N 37° W 94.22 F Et USE S 48° W 94.98 F	. 25863" WITNESSED EET EET (NOTE: NOT THE :	SAME						'HE RO <i>i</i>	
7/8" X 30		H 4" DIAMETER (T N-R6W South 2.93 F	EET	P.A.	теа . 34:	by I 5 Ion	~e <mark>e</mark> r ia Co	Group unty)		
	DISTANCE NORTH TO A-9 = 2633.23 FEET DISTANCE SOUTH TO A-11 = 2633.23 FEET						Date 8-19-38						
				MARINUS A MULDER CANO						nairmai	 n		
· 9	namila.	Mules		SURVEYOR		ع							

THE STATE OF

Surveyor's Michigan License No. ___