SURVEY & REMONUMENTATION

JAN 2 0 1999

LAND CORNER RECORDATION CERTIFICATE

SECTION	Filing Requirement of Act 74,	Mich. P.A. 1970	. Å	page C	E,			
For corners in IONIA	Located In: Corner Code #			Paul L				
(County)	STATE OF MICHISAN							
Public Land Survey	T6 <u>N R5W</u> A-9				VEO FO		RD	
	TR			25 NOV	98 2	:59 P.	M.	
2. Property Controlling S	T R	Registe	egister of Deeds Stamp & File Number					
4. Lot No , Recorded Plat			. B C	; D E	: F C	: H I	J K	ı M
5. Private Claims			6	5	4	3	2	1
MANUA MUNDED	, , , , , , , , , , , , , , , , , , ,	3	_			10	11	10
do hereby certify that under requi	, in a field survey on <u>JUNE 23</u> ements of P.A. 74, Michigan P.A. of 1970, the corruptormance with regulations and rules therefore	ner points mentioned in 5	7	8	9	10	11	12
current manual of survey instruction	ons of the United States Department of the Introduction of the Int	erior, Bureau of Land 6	18	17	16	15	14	13
above were in conformance with Court of Law; established, re	the rules of the Michigan Board of Land Surveyor-established, monumented, re-monumented,	ors or by a Decree of a recovered, found as 8	19	20	21	22	23	24
expressed below: NOTE: Not more than 4 corners, a	II in the same town and range, may be recorded	9 10	30	29	28	27	26	25
on this certificate.		11 · 12	31	32	33	34	35	36
U.S. DEPUTY SURVEYOR LUCIUS LYO	d accessories and/or subsequent restoration: IN IN 1827 SURVEYED PORTLAND TOWNSHIP. LYO	13 lins when running				,		
LINE BETWEEN SECTIONS 19 AND 3 BEECH S 84° W 24 LINKS AND A 36	O CLOSED AT THE ESTABLISHED CORNER (M·9) FOI ' Lynn n 44° w 42 Links.	R TOWNSHIP T6N-R6W, BEING	G A WOO	D POST	WITNE	SSED B	Y A: 18	in .
APPROXIMATELY 24" LONG FOR HIS WITNESS NOTES FOR A-9: 10" ELM	INTY SURVEYOR REMONUMENTED PORTLAND TOV MONUMENTATION. IN THE COUNTY SURVEYORS N 38 1/2° E (NO DISTANCE GIVEN) AND A 10" SUG ION IMPROVED AND PAVED KEEFER HIGHWAY IN 1	COPY OF THE G.L.O. NOTES O AR MAPLE S 65 1/2° W 61 LIN	N PAGE NKS (40.	57 CRA	WFORD	HAS M		AL.
	ESS NOTES TO A-9 IN THE WITNESS INDEX SHEETS CORNER FENCE POST N.W. 44.80 FEET.	S AS FOLLOWS: POST N.E. 42.	.20 FEE	T; CORN	ER FENI	CE POS	Γ S. E. 33	3.10
AT THE INTERSECTION OF GIBBS RO	and/or method applied in restoring or reestablishing comer DAD AND KEEFER HIGHWAY EXCAVATED THE ROAD DEPTH OF 30" FOUND A 3/4"x12" BOAT SPIKE IN A	BED AND FOUND A 3/4"x10"						
	and accessories established to perpetuate locating the posi IAMETER ALUMINUM CAP STAMPED "IONIA COUN"		LACE OF	THE EX	ISTING	MONUI	MENTAI	ΓΙ ΌΝ
	TH SIDE 36" MAPLE \$ 72° W 38.45 Th Side 20" Maple N 71° W 90.14		-					
	HWEST SIDE 40" MAPLE N 15° W 111.5	52 FEET	Ratified by Peer Group P.A. 345 Ionia County					
	MARINUS MULDER CAND CAND SUITAEVO			<i>\$ -</i> is A. I				
Signed by Marrix C	muller 25000 Bate	11-11-98	3					
Surumuer's Michigan License No.	E963) ki	SDD OF LABOR	Substrant :	.m. 20 447*			