\$7<u>`</u>7

## LAND CORNER RECORDATION CERTIFICATE

LIBER 4 PAGE 98

	Fil	ling Requirement of Act 74, Mi	ch. P.A. 1970							
For corners in SECTION  IONIA (County)	Located In:	Corner Code #				IO	OF NIO NIA COU VED FOO		an ka	
1. Public Land Survey	T6_N R7_W	G-4		23 NOV 99 3:02 P.H.						
2. Property Controlling S	TRTRTRTRTRTRTRTRTR		- - - - Reg	DIANE N. ADAMS REGISTER OF DEEDS Register of Deeds Stamp & File Number						
							,			
4. Lot No, Recorded Pla 5. Private Claims				i r				, ,	J K	
				3	6	5	4	3	2	1
t, MARINUS MULDER do hereby certify that under requi	, in a field surve	ey on <u>JUNE 16</u> 19 99 . Higan P.A. of 1970, the corner r	points mentioned in	4	7	. 8	9 (	10	11	12
lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5					18	17	16	15	14	13
above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as					19	20	21	22	23	24
NOTE: Not more than 4 corners, all in the same town and range, may be recorded				10	30	29	28	27	26	25
On this certificate.  A. Description of original monument and accessories and/or subsequent restoration:			11 -	31	32	33	34	35	36	
THIS CORNER WAS FIRST ESTABLIS WAS SET WITNESSED BY A 12" SUPPERPETUATION: D.C. CRAWFORD FOR S88 OF IONIA COUNTY SURVEY REC	SHED BY U.S. DEPUTY SU GAR MAPLE N 04° E 17 L ORMER IONIA COUNTY S	URVEYOR JOHN MULLETT IN 183 LINKS, AND A 5" BEECH N 09° W SURVEYOR PERFORMED A SURVE	V 20 LINKS.	<sub>13</sub> ∟ NGUS	ST 1, 1	899 REI	CORDED	IN VOLU	JME 2, P	PAGE
THE IONIA COUNTY ROAD COMMIS	SION IMPROVED AND PA	WED JORDAN LAKE ROAD IN 190	65							
THE IONIA COUNTY ROAD COMMIS	SION HAS WITNESSES FO	OR G-4 ON THE WITNESS INDEX	SHEETS BUT THEY	ARE IL	LEGIBI	LE.				
B. Description of corner evidence foun AT A DEPTH OF 3" BELOW THE PAV FOUND A 3/4" x 12" BOAT SPIKE NE	ED SURFACE AND OPPOS		EST FOUND A NAIL	& WA	SHER.	BELOW	'NAIL A	T A DEP	TH OF 2	:5"
REPLACED BOAT SPIKE WITH A 7/8' BOX WITNESSED BY:	" x 24" STEEL ROD WITH	to perpetuate locating the position o I A 4" DIAMETER CAP STAMPED		RVEY	MONU	MENT -	P.S. 25	863" IN	A MONU	JMENT
N&T SOUTH SIDE 30" MAPLE N&T SOUTH SIDE WOOD POST N&T SOUTH SIDE WOOD POST N&T NORTHEAST SIDE 3" ASH	WEST 28 N 32° W	3.20' 42.49'	,							
Signed by Mard	a Muld	Date	//-3	9	9	,				
Surveyor's Michigan License No. 2	25863		FORM APPROVED BY MICHIGAN STA	ATE BOARD	OF LANDS	urveyors, J		D FOR WORD ?		IAY 14, 1975 O JAN, 1983 IARCH, 1993
Ratified by Peer Gro P.A. 345 Ionia Coun	วย <b>p</b> rty	MARINUS A								

Date August 18, 1999
Marinus A. Mulder, Chairman

