REMONUNATION

DEC 1 6 1996

LAND CORNER RECORDATION CERTIFICATE

LIBER 3 PAGE 277

Filing Requirement of Act 74, Mich. P.A. 1970

For corners in	. · · ·									
10NIA Located In:		Corner Code #	Corner Code #			10	OF AII NIA CON NED FON		2D	
1. Public Land Survey	T6N R7W	I - 6	_		;	21 NOV	96 2	108 P.H	. .	
2. Property Controlling S	T R T R T R		_ _				E H. A	IDAMS DEEDS	_	
in Section S	T R R R R R R R R R R R R R R R R R R R		Reg	jiste	r of D		,		Numbe	er .
4. Lot No, Recorded Pl 5. Private Claims	at		-	1 A	В	C D	E F	Э Н	IJK	L M
				2	. 6	5	4	3	2	1
I. MARINUS MULDER				3	7	8	.9	10	11	12
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land					18	17	16	15	14	13
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, ‡ and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Degree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:					19	20	21	22	23	24
NOTE: Not more than 4 corners,	all in the same town an	d range, may be recorded		9 10	30	29	28	27	26	25
on this certificate. A. Description of original monument	and accessories and/or sul	sequent restoration:		12	31	32	33	34	35	36
THIS CORNER WAS FIRST ESTABL WAS SET WITNESSED BY A 15" E PERPETUATION: FORMER IONIA C PAGE 88 OF THE IONIA COUNTY S	EECH SOUTH 14 LINKS COUNTY SURVEYOR, TH	AND A 8" BEECH N 27° E 7 LINKS OMAS CORNELL PERFORMED A SI	3. Urvey of Section 1	5, DE				DED IN 1	/OLUME	1,

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

EXCAVATED ROAD BED OPPOSITE 1/4 LINE FENCE RUNNING EAST WITH A BACK HOE BUT FOUND NO SUBSTANTIAL EVIDENCE. SE I-6 ON LINE BETWEEN THE NORTHEAST CORNER OF SECTION 15 AND OPPOSITE THE 1/4 LINE FENCE RUNNING EAST.

DISTANCE FROM I-5 TO I-6 = 2648.10 FEET DISTANCE FROM I-6 TO I-7 = 2642.07 FEET

Surveyor's Michigan License No. 25863

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner: SET A 3/4" X 36" STEEL ROD WITH A 2 3/4" DIAMETER CAP STAMPED "IONIA COUNTY - 25863"

WITNESSED BY:

NAIL & TAG EAST SIDE 12" TWIN HICKORY S 14° W 129.94 FEET P.K. NAIL & TAG EAST SIDE POWER POLE N 19° E 131.42 FEET P.K. NAIL & TAG WEST SIDE POWER POLE N 48° E 177.69 FEET NORTHWEST CORNER HOUSE FOUNDATION N 64° E 195.78 FEET

Ratified by Peer Group P.A. 345 ionia County Daie 1/-/3-96 Marines A. Meldar, Guairman



Signed by	mesa	mulch	Dat	e NOVEMBER	20,	1996
-						