JAN 1 3 2000

Same of the second

CECTION

LAND CORNER RECORDATION CERTIFICATE

ERTIFICATE
LIBER 4 PAGE 83

	JW.	Filing Requirement of Act 74, N	fich. P.A. 1970		JOY PRO JOSE			
For corners in 10NIA (County)	Located In:	n: Corner Code # STATE OF MICHIGAN IONIA COUNTY RECEIVED FOR RECORD						
1. Public Land Survey				23 NOV 99 2:57 P.M.				
2. Property Controlling	T R S T R		•		DIANE M. REGISTER			
in Section 3. Miscellaneous	S T R S T R		Regi	ster of D	eeds Stan	np & File	Numbe	r
Property in Sec. 4 Lot No	\ _			A D	C D E	- C U		1 M
5. Private Claims				1 A B 2 6		1 3	2	1
				3				
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:				4 7 5 7	-	10	11	12
				6 18	17 1	6 15	14	13
				8 19	20 2	1 22	23	24
	corners, all in the same town a	nd range, may be recorded		10 30	29 2	8 27	26	25
on this certificate	e. - mixment and accessories and/or st	absequent restoration		12 31	32 3	3 34	35	36
THIS CORNER WAS FIRST WAS SET WITNESSED BY A PERPETUATION: A.C. SMIT PAGE 154 OF IONIA COUNTY ROAD THE IONIA COUNTY ROAD A: 16" HICKORY N 42° E 5 B. Description of corner evid AT THE INTERSECTION OF SURFACE FOUND A 5/8" x	ESTABLISHED BY U.S. DEPUTA: 9" BEECH N 24° E 28 LINKS TH FORMER IONIA COUNTY SUBTY SURVEY RECORDS. SMITH COMMISSION IMPROVED NAS COMMISSION HAS WITNESSI 7.55 FEET; 26" OAK S 58° W Jence found and/or method applied NASH HIGHWAY AND PORTL 20" ROD WITH A 2" DIAMETE for corner and accessories estable PIPE WITH A 7/8" x 24" STEEL ISED BY: KORY N 42° E 57.61 IN 53° W 63.72 FEET	Y SURVEYOR JOHN MULLETT IN 1 S AND A 12" WHITE OAK S 12° E S URVEYOR PERFORMED A SURVEY OF RECORDED THAT A STONE WAS SH HIGHWAY CIRCA 1949. NO SP ES FOR H-11 FOUND IN THE SECTION OF SECTI	3 LINKS. DF SECTION 34, DECEM THE MONUMENTATION ECIFIC INFORMATION C ON CORNER INDEX SHE 5.82 FEET. DN WITNESS REMAINS ELOW THE ROD FOUND n of the corner:	FOR H-11 COULD BE F SETS. A 1/2 BEING THE A 1/2" x 1	. NO WITNE OUND ON TI 2" PIPE IS CA E HICKORY T 8" PIPE NEX	SSES WERI HE ROAD PI ALLED FOR REE N.E. A T TO A STO	E GIVEN. ANS FO WITNESS T THE P. DNE.	R H-11. SED BY
	DUNTY HIGHWAY PROJECT M							
Orginol D)	& C. Middle	Date	11-3-99		avalleyana	1921		
Date Septem	Peer Group	MARIBUS A.	FORM APPROVED BY MICHIGAN STA	IE DUANU UF LAND		ADAPTED FOR WORL	REVIS	MAY 14, 1925 ED JAN, 1983 MARCH, 1983