LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

LIBER 003 PAGE 226

For corners in IONIA (County)

STATE OF MICHIGAN
IONIA COUNTY
RECEIVED FOR RECORD

16 NOV 95 4:22 P.M.

DIANE M. ADAMS
REGISTER OF DEEDS

Register of Deeds Stamp & File Number

	Located In:	Corner Code #
1. Public Land Survey	T7N R8W	F-3
	T R	
	T R	
	T R	
2. Property Controlling	S T R	
in Section	S T R	
3. Miscellaneous	S T R	
Property in Sec.	S T R	

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2			6	5	4	3	2	1					
3													
4			7	8	9	10	11	12					
5													
6			18	17	16	15	14	13					
7													
8			19	20	21	22	23	24					
9													
10			30	29	28	27	26	25					
11													
12			31	32	33	34	35	36					
13													

I, MARINUS MULDER, in a field survey on AUGUST 1 1995, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:
THIS CORNER WAS FIRST ESTABLISHED BY U.S. DEPUTY SURVEYOR NOAH BROOKFIELD IN 1837. A WOOD POST WAS SET WITNESSED BY A 12" HICKORY S 8° E 8 LINKS & A 10" WHITE OAK N 46° E 44 LINKS.
PERPETUATION: THOMAS CORNELL FORMER IONIA COUNTY SURVEYOR PERFORMED A SURVEY OF SECTION 4, NOVEMBER 15-20, 1877 FOUND IN LIBER 1, PAGE 256 OF THE IONIA COUNTY SURVEYORS RECORDS. CORNELL STATES THAT HE SET A STONE WITH THE GOVERNMENT BEARING TREES FOR WITNESSES. PROFESSIONAL SURVEYOR, EDWARD GLAZA NO. 9548 RECORDED F-3 APRIL 16, 1990 FOUND IN LIBER 2 PAGE 385 OF RECORDED CORNERS. GLAZA SET A CAPPED IRON 2 FEET NORTH OF CENTERLINE AND 2 FEET WEST OF A FENCE LINE TO THE NORTH.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:
EXCAVATED HARKNESS ROAD OPPOSITE A FENCE LINE TO THE NORTH AND FOUND A POINTED STONE 12" BELOW GRAVEL SURFACE WITH A SMALL STONE PILE ON TOP. FOUND A 1/2" ROD AND CAP SET BY EDWARD GLAZA 3 FEET NORTH AND 2 FEET MORE OR LESS WEST. ACCEPTED THE STONE AS THE CORRECT CORNER.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:
SET A 3/4" X 24" STEEL ROD WITH A 2 3/4" DIAMETER CAP NEXT TO THE STONE WITNESSED BY:
NAIL & TAG WEST SIDE 34" TWIN OAK NORTH 19.42 FEET
NAIL & TAG WEST SIDE 48" TWIN CHERRY S 15° E 24.33 FEET
NAIL & TAG NORTHWEST SIDE 32" MAPLE S 64° W 36.10 FEET
NAIL & TAG SOUTH SIDE 10" OAK N 77° E 43.80 FEET

Ratified by Peer Group
P.A. 345 Ionia County

Date Nov. 1, 1995
Marinus A. Mulder, Chairman

Signed by Marinus A. Mulder Date 11-14-95

Surveyor's Michigan License No. 25863

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 1971
REVISED MAY 14, 1975
REVISED JAN., 1983
ADAPTED FOR WORD PROCESSING MARCH, 1993