SURVEY & REMONUMENTATION

JAN 2 0 1999

Surveyor's Michigan License No. 25863

JAN 20 1999 LAND CORNER RECORDATION C	ERTIFICATE						
SECTION Filing Requirement of Act 74, Mic	:h. P.A. 1970	eco 4	PACE	F.Ç			
For corners in IONIA Located In: Corner Code #		. L'Ait T	LUM	ya i			
(County)			STAT	E OF H	TCH (BA)	Ų	
1. Public Land Survey T7 N R7 W G-5			1	enia c	DUMTY		
T R	_		i ion	TEO F	进 性机	UNU	
T R			25 NO	IV 98	2:57 P	.М.	
2. Property Controlling S T R in Section S T R 3. Miscellaneous S T R	_			IAHE H.			
3. Miscellaneous S T R		ter of I	Deeds S	tamp 8	k File 1	Nümbe	r
4. Lot No, Recorded Plat							
5. Private Claims	- .	<u> </u>	СЬ	1			·
		² 6	5	4	3	2	1
I, MARINUS MULDER , In a field survey on AUGUST 19, 19 9 8 ,		4 7	8	9	10	11	12
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner plines 1 and 2 above were in conformance with regulations and rules therefore a	s required in the	5 18	17	16	15	14	13
current manual of survey instructions of the United States Department of the Interior Management or by a decree of a Court of Law and/or that the corner points mentioned	in lines 3, 4 and 5	7 "	<u> ''</u>	10	13	14	
above were in conformance with the rules of the Michigan Board of Land Surveyors of Court of Law; established, re-established, monumented, re-monumented, recognition expressed below:	vered, found as	в 19	20	21	22	23	24
		0 30	29	28	27	26	25
NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.		1					
A. Description of original monument and accessories and/or subsequent restoration:	1	$\begin{bmatrix} 2 & 31 \\ 3 & & \end{bmatrix}$	32	33	34	35	36
THIS CORNER WAS FIRST ESTABLISHED BY U.S. DEPUTY SURVEYOR ORANGE RISDON IN 18 POST WAS SET WITNESSED BY A 18" ELM S 61° E 59 LINKS AND A 12" WHITE OAK N 61°							
PERPETUATION: THOMAS CORNELL FORMER IONIA COUNTY SURVEYOR PERFORMED A SURVEY OF SECTION IONIA COUNTY SURVEYORS RECORDS. CORNELL SAID HE SET A STONE AND STAKE WITNER AND A 3" WHITE OAK N 34 1/4° W 70 LINKS (46.2 FEET). CORNELL ALSO PERFORMED A SURVEY IN SECTION 9 MARCH 1878 RECORDED ON PAGE 27 CORNELL SHOWED NO ADDITIONAL INFORMATION FOR G-5. D.C. CRAWFORD ALSO PERFORMED A SURVEY OF SECTION 15 IN SEPTEMBER OF 1889 RECORDED.	SSED BY A 12" WHITI 74 OF VOLUME 1 OF TH	E OAK N	39 3/4° \	W 154 LI Survey	NKS (1 'ORS RE	01.64 FI Cords.	EET)
RECORDS. CRAWFORD DID NOT RECORD WHAT WAS SET OR FOUND FOR G-5.	UKUEU UN PAGE 58 VI	JLUME A	OF INE	IUNIA GI	JUNIT	POHVET	OHO
THE IONIA COUNTY ROAD COMMISSION IMPROVED BELLAMY ROAD IN 1969. THE INFORM WITNESSES ARE 1 1/4" PIPE: 28" STUMP S.E. 40.45 FEET; 20" OAK N.E. 44.50 FEET; SIGN						34-64. T	THE
REGISTERED LAND SURVEYOR DAVID CLIFFORD NO. 25837 RECORDED G-5 DECEMBER 1980 RECORDS. CLIFFORD FOUND A BOAT SPIKE FROM THE IONIA COUNTY ROAD COMMISSION N.E. 61.57 FEET; NAIL 24" OAK E.N.E. 93.62 FEET; NAIL POWER POLE W.S.W. 34.73 FEET; N	WITNESSES. CLIFFOR	D'S WIT	NESSES 1	TO G-5 V			OPLAI
B. Description of corner evidence found and/or method applied in restoring or reestablishing corner: AT THE INTERSECTION OF BELLAMY ROAD AND LYLE ROADS MEASURED TWO OF CLIFFORD'S WIFUUND A 3/4" BOAT SPIKE. BELOW BOAT SPIKE FOUND A 1" X 15" SOLID STEEL SHAFT 18" DEEF 32". ACCEPTED THIS AS THE PERPETUATED CORNER.	ITNESS DISTANCES AND P. BELOW THIS FOUND A	EXCAV	ATED THE Next to	ROAD B	ED. AT Stone	A DEPTI At a de	1 OF 6' PTH OI
C. Description of monument for corner and accessories established to perpetuate locating the position of REPLACED THE BOAT SPIKE, 1" STEEL SHAFT, AND 2" PIPE WITH A 7/8" x 24" STEEL ROD WITNESSED BY:		CAP ST	ÁMPED "	IONIA CO	OUNTY-I	P.S. 258	63"
NAIL & TAG NORTH SIDE TWIN 24" OAK N 82° E 93.27 FEET NAIL & TAG NORTH SIDE POWER POLE S 83° W 34.70 FEET		Ra ₽	atified	by F	eer (Group)
CENTERLINE STREET SIGN N 42° E 49.96 FEET	P.A. 345 Ionia County						
NORTH EDGE NORTH LEG OF "ARROW" ROAD SIGN N 70° W 25.04 FEET	Lind Discourse Control of the Contro	<u>Da</u> Ma	rinus A	9 – / . Muld			
Signed by Marcuil a Muldan Date	11-11-98	3					