

## JAN 2 5 1996

## COMMISSION

Surveyor's Michigan License No. 25863

## LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970 PER 003 PAGE 232

COlausio	Filing Requir	ement of Act 74, Mich.	. Р.А. 19 <i>7</i> 0	I BER	VV	J PA	GE 🚣 🖢		,		
For corners in IONIA	I manaka di tiron	G. 0.1 #	1								
(County)	Located In:	Corner Code #	Corner Code #		STATE OF MICHIGAN						
						IU	NIA CO	YTML	•		
Public Land Survey	TO M DE W	۲ 10				RECEI	VED FOI	R RECO	RD		
i. Fublic Land Survey	T R	T8 N R5 W E-12 T R 16 NOV 95 4:26 P.M.									
	TR				,	io Nuv	95 4	Z0 F.	1.		
	' K					ħΙΔΙ	NE M. I	2HAR			
Property Controlling     in Section	S T R						STER O		3		
	S T R S T R		Reg	jister	of D		tamp			er	
	S T R		<u> </u>								
<ol> <li>Lot No, R.</li> <li>Private Claims</li> </ol>	ecorded Plat		<del></del>	ı A	В	C D	E F	G H	1 J 🕏	C L	
o. Theate Claims			<del></del>	2	6	5	4	3	2	1	
				3 -			4	٥		'	
I MARINIIS MIIIDE	R in a field ourse	won Alichiet 99 tan	r.	4	7	8	9	10	11	12	
do hereby certify that under	R , in a field surve requirements of P.A. 74, Michigan F	P.A. of 1970, the corner points	mentioned in	5				10	<u> </u>		
lines 1 and 2 above were	in conformance with regulations tructions of the United States De	and rules therefore as requ	uired in the	6	18	17	16	15	14	13	
	of a Court of Law and/or that the o			7			ļ			<u> '</u>	
above were in conformance	with the rules of the Michigan Book, re-established, monumented,	ard of Land Surveyors or by a	Decree of a	8	19	20	21	22	23	24	
expressed below:	re-established, monumented,	re-monumented, recovered,	, lourid as	9						<b> </b>	
*10*** N			_	10	30	29	28	27	26	25	
NOTE: Not more than 4 on this certificate	corners, all in the same town a	and range, may be recorded	ď	31 }-						<del> </del>	
on the outeroact	•			12	31	32	33	34	35	36	
	al monument and accessories a	•		13 L			i			L	
	evidence found and/or methol D BED (STRUBLE ROAD NO					E GOIN	NG EA	1A TS	<b>1D</b> W!	EST	
	FOUND A PILE OF STONES F THE ORIGINAL CORNER.		ERY WITHI	N ST	TONE	PILE.	. ACC	EPTE	D THI	S AS	
SET A 3/4" X 36" STEE OF THE STONE PILE WI NAIL & TAG EAST SIDE NAIL & TAG NORTH SID NAIL & TAG WEST SIDI	ment for corner and accessories. L ROD WITH A 2 3/4" DIA TNESSED BY: E 4" HICKORY S 17° W 11. DE 32" OAK S 85° W 12.02 E 10" HICKORY N 60° E 12 E 8" TWIN HICKORY N 3° E	METER CAP STAMPED  20 FEET 2 FEET 1.22 FEET	"IONIA CO	ified 34:	Y P. 1 by 5 10	Peernia C	863"   Gro. Count	N THI	E CEN	ITER	
Signed by Mari	il a mulcla	Date	11-1	14	-7	<u>5</u> —					