SECTION

## LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

For corners in IONIA (County)	Located In:	Corner Code #	B4 153 1		LIE	BER 4		page 10	63				
1. Public Land Survey	T R						STATE OF MICHIGAN IONIA COUNTY RECEIVED FOR RECORD  22 NOV 2000 2:16:28 PM						
T						DIANE M. ADAMS REGISTER OF DEEDS  egister of Deeds Stamp & File Number							
4. Lot No , Recorded Plat				_	A B	C D	E F (	} H €	JK	L M			
5. Private Claims			<del>.</del>	2	6	5	4	3	2	1			
				3 4	<u> </u>	,	`						
t, MARINUS MULDER , in a field survey on JULY 6, 2000, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:					7	8	9	10	11	12			
					18	17	16	15	14	13			
					19	20	21	22	23	24			
NOTE: Not more than 4 corners, all in the same town and range, may be recorded			9 10	30	29	28	27	26	25				
on this certificate.				11 12	31	32	33	34	35	36			
A. Description of original monument and accessories and/or subsequent restoration: THIS CORNER WAS FIRST ESTABLISHED BY U.S. DEPUTY SURVEYOR, ROBERT CLARK ON FEBRUARY 16 1831 A WOOD POST WAS SET AND WITNESSED BY A 13" WHITE OAK N 80° E 32 LINKS, AND A 9" WHITE OAK N 81								L					
PERPETUATION: THERE IS NO RECOR	RDED COUNTY SURVEY	' INFORMATION FOR D-1	3.										
THE IONIA COUNTY ROAD COMMISSION IMPROVED AND PAVED NICKLE PLATE HIGHWAY IN 1959. THE ROAD PLANS WITNESSES ARE AS FOLLOWS: 36" ELM S.E. 49.62 FEET; 24" MAPLE N.W. 47.10 FEET; 24" MAPLE N. 32.35 FEET; 107' EAST TO D-1, T7N-R6W.													
THE IONIA COUNTY ROAD COMMISSION HAS WITNESSES FOR D-13 IN THE WITNESS INDEX SHEETS AS FOLLOWS: 2" IRON PIPE WITNESSED BY; 24" MAPLE NE. 73.00 FEET; 36" MAPLE NE. 46.50 FEET; 36" MAPLE NORTH 31.75 FEET; 40" ELM SOUTH 25.4 FEET.													
REGISTERED SURVEYOR, RICHARD CRATER RECORDED D-13 SEPTEMBER 1, 1972, FOUND IN LIBER 1 PAGE 46 OF ACT 74 RECORDS. CRATER FOUND A NAIL & WASHER WITNESSED BY: NORTHWEST CORNER CONCRETE DRIVE S 55° E 61.95 FEET, NORTH 1/4 CORNER SECTION 5, T7N-R6W, EAST 106.60 FEET.  B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:													
NO COUNTY WITNESSES REMAIN. MEASURED CRATER'S WITNESS; CONCRETE DRIVE S.E. 61.95 FEET AND FOUND REMAINS OF A NAIL & TAG UNDER THE PAVED SURFACE. BELOW NAIL & TAG FOUND A 7/8" X 16" ROD. BELOW 7/8" ROD FOUND A 2" PIPE NEXT TO A LARGE STONE AT A DEPTH OF 24". FENCE LINE RUNS NORTH FROM THE RIGHT OF WAY LINE.													
C. Description of monument for corner REPLACED EXISTING MONUMENTAT WITNESSED BY:	and accessories establishe TON WITH A 7/8"x24"	ed to perpetuate locating the STEEL ROD WITH A 4" D	position of the corner: AMETER ALUMINUM CA	STAM	PED "II	ONIA CO	UNTY -	P.S. 258	3 <b>63</b> ″				
NAIL & TAG NORTH SIDE 14 NAIL & TAG SOUTHEAST SII NAIL & TAG NORTHWEST SI NAIL & TAG NORTH SIDE 22 N. 1/4 CORNER SECTION 5, T7N-R6V Signed by Marux C	DE 26" ELM NORTH DE 8" ELM S 54° V " ELM	28.76 FEET V 36.65 FEET S 73° E 7 AP EAST											
Surveyor's Michigan License No. 25863 FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 20, 1971 REVISED MAY 14, 1976													
	Junion W	NUMBER OF MICHIGANIA		đ	atifi	.: Q	ADAPT	EO FOR WORD	REYISI Processing 1	ED JAN., 1983 MARCH, 1993			



Ratified by Peer Group P.A. 345 Ionia County

Date 9-21-2003 Marinus A. Mulder, Chairman