Date September 9, 1999 Marinus A. Muneci, Chairman

LAND CORNER RECORDATION CERTIFICATE

|  |  |   | f Act 74, Mich. P.   |  | LIBER           | 4   | PAGE .             | 110                  |                    |                      |                        |
|--|--|---|--|--|-----------------|---|--------------------|----------------------|--------------------|----------------------|------------------------|
| For corners in IONIA   | Located in:  | Corner Code #   | , ,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,                              |  |                 |   | IC                 | OF HI                | UNTY               |                      |                        |
| 1. Public Land Survey  | T <u>8 N</u> R <u>7 W</u><br>T R                                     |   | C-2  |  |                 | RECEIVED FOR RECORD  23 NOV 99 3:06 P.M.  |                    |                      |                    |                      |                        |
| 2. Property Controlling S  | T R  |   |  | Reg                                    | giste           | r of D                                    | REGI               | NE N. 1<br>STER OF   | F DEED!            |                      | r                      |
| 4. Lot No , Recorded Plat  |  | •   |  |  |                 | ħ   | 0 D                | E F G                | <b>-</b> u i       | ı V                  | ı                      |
| 5. Private Claims  |  |   |  |  | 2               |   | 5                  | 4                    | 3                  | 2.                   | 1                      |
|  |  |   |  |  | 3               | 6   | 5                  | 4                    | ა                  | ∠ .                  |                        |
| 1, MARINUS MULDER , in a field survey on JUNE 16 1999, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the |  |   |  |  | 4<br>5          | 7   | . 8                | 9                    | 10                 | 11                   | 12                     |
| current manual of survey instructions  Management or by a decree of a Courabove, were in conformance with the  | of the United Stat<br>It of Law and/or that<br>Irules of the Michiga | es Department o<br>at the corner points<br>an Board of Land | of the Interior, Bure<br>is mentioned in line<br>I Surveyors or by a | eau of Landes 3, 4 and 5 a Decree of a | 6<br>7<br>8     | 18  | 17<br>20           | 16<br>21             | 15<br>22           | 23                   | 13<br>24               |
| Court of Law; established, re-es expressed below:  | stablished, monum  | ented, re-monum   | ented, recovered   | , found as                             | 9               |   |                    |                      |                    |                      |                        |
| NOTE: Not more than 4 corners, all in on this certificate.   | the same town and r  | ange, may be record   | led  |  | 10<br>11        | 30  | 29                 | 28                   | 27                 | 26                   | 25                     |
| A. Description of original monument and ac<br>THIS CORNER WAS FIRST ESTABLISHED<br>POST WAS SET WITNESSED BY A: 30"  | D BY U.S. DEPUTY SI  | JRVEYOR NOAH BR   |  | . A W00D                               | 12              | 31  | 32                 | 33                   | 34                 | 35                   | 36                     |
| PERPETUATION: D.C. CRAWFORD FORM<br>PAGE 322 OF COUNTY SURVEY RECORD   | DS. CRAWFORD FOU   | ND THE OLD 1/4 PC   | DST AND SET A ST   | AKE AND STO                            | NE.             |   |                    |                      |                    |                      | UME                    |
| CRAWFORD PERFORMED A SURVEY OF CRAWFORD'S WITNESSES FOR C-2 WEB  | SECTION 5, MARCH<br>RE" 2" WHITE OAK N                               | 11, 12, & 13, 189<br>23° W 67 LINKS (4                      | 1 RECORDED IN VO<br>14.22 FEET) AND 6'                               | LUME 2, PAGE<br>' WHITE OAK S          | 172 (<br>3 42 1 | )F COU<br> 2° W                           | INTY SU<br>65 LINK | RVEY RE<br>S (42.9 I | ECORDS.<br>FEET).  | •                    |                        |
| THE IONIA COUNTY ROAD COMMISSION   | N IMPROVED JOHNS   | ON ROAD IN CIRCA  | 1963   |  |                 |   |                    |                      |                    |                      |                        |
| THE IONIA COUNTY ROAD COMMISSION<br>BOAT SPIKE WITNESSED BY 15" OAK S  |  |   |  | FOR A LARGE S                          | STONI           | E BROU                                    | JGHT UI            | WITH A               | N OAK              | STAKE                | AND                    |
| PROFESSIONAL SURVEYOR GARY BILOV<br>SPIKE 18" BELOW THE ROAD SURFACE<br>D.N.R. CAP ON A 1/2" x 24" ROD INSIDI<br>S 40° W 43.48 FEET; NAIL IN UTILITY I<br>SPIKE OVER P.K. NAIL N 15° E 17.12 FE  | AT THE CALLED FOR<br>E A 3/4" PIPE IN A M<br>POLE N 69° W 66.32      | R DISTANCE OF CRA<br>ONUMENT BOX, W                         | AWFORD'S 1891 W<br>ITNESSED BY: NAII                                 | ITNESS TO AN<br>. & TAG 10" O          | I OAK<br>AK S   | SOUT<br>34° E                             | HWEST.<br>67.64 FI | BILOW<br>ET; NAI     | SET A 4<br>L & TAG | " DIAMI<br>39" 0A    | K<br>K                 |
| 8. Description of corner evidence found an FOUND BILOW'S IRON AS CALLED FOR. WITNESSES REMAIN. ACCEPTED THIS   | REMOVED IRON AN  | D EXCAVATED TO  | hing corner:<br>A DEPTH OF 4' 6" I                                   | BUT FOUND NO                           | STO             | NE. N                                     | O COUN             | TY ROAE              | COMM               | ISSION               |                        |
| C. Description of monument for corner and REPLACED BILOW'S IRON AND CAP WIT MONUMENT BOX WITNESSED BY:  N&T EAST SIDE 25" OAK  N&T NORTHEAST SIDE 10" PINE  D.N.R. REFERENCE TAG EAST SI  N&T EAST SIDE UTILITY POLE   | TH A 7/8" x 30" STEE<br>N 45° E 93.68 FEE                            | EL ROD WITH A 4"  <br>T<br>51.66 FEET<br>43.50 FEET         | ng the position of the<br>DIAMETER CAP ST                            | corner:<br>AMPED "IONIA                | COUI            | NTY SI                                    | URVEY N            | AONUME               | NT - P.S           | 3. 25863<br>3. 25863 | 3" IN 1                |
| Signed by  | . Mule   | le_   | Date   | 1/-3                                   | ; —             | 90  | ;                  |                      |                    | <del> </del>         |                        |
| Surveyor's Michigan License No. 258  |  |   | FORM A   | PPROVED BY MICHIGAN S                  | STATE BOA       | IRD OF LANG                               | ) SURVEYORS,       | JAN. 28, 1971        |                    | REVISED              | MAY 14, I              |
| Ratilied by<br>P.A. 345 id   | Peor Group   | ,   | Striket.   | MARINUS                                |                 | A. C. |                    | ADAPT                | ED FGR WORD        | REVIS<br>Processing  | EB JAN., 1<br>MARCH, 1 |