050181996

LAND CORNER RECORDATION CERTIFICATE

LIRER 3 PAGE 283

A 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	13.81	SSION	
1 38 1	17117.781	1 6 3 6 C	

Filing Requirement of Act 74, Mich. P.A. 1970

For corners in IONIA Located In: (County)		in:	Corner Code #				IONI	F MICH A COUN D FOR					
1. Public Land Survey		T8N T	R7W R	Н-3						9 P.M.			
Property Controlling in Section Miscellaneous	\$ \$	T T T T	RRRRRRRR			•-4-		REGIST	M. AD ER OF	DEEDS			
Property in Sec.	s	' <u></u>	R		Keg	Register of Deeds Stamp & File Number							
4. Lot No, R 5. Private Claims	ecorded Plat _					1 / 2 /	A . B .	C D 5	E F (Э H 3	1 J K	L M	
I. MARINUS MULDER		, in a	a field surve	ey on <u>SEPTEMBER 18</u>	1996,	4	7	8	9	10	11	12	
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5					5 6 7	18	17	16	15	14	13		
above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:				, 8 9	19	20	21	22	23	24			
NOTE: Not more than 4		in the same	e town and t	range, may be recorded		10	30	29	28	27	26	25	
A. Description of original n		accessories	and/or subse	quent restoration:		12 13	31	32	33	34	35	36	

THIS CORNER WAS FIRST SET BY US DEPUTY SURVEYOR NOAH BROOKFIELD IN 1837. A WOOD POST WAS SET WITNESSED BY A 8" WHITE DAK S 77° E 8 LINKS AND A 12" WHITE OAK N 28° W 26 LINKS.

PERPETUATION: D.C. CRAWFORD FORMER IONIA COUNTY SURVEYOR WROTE MARGINAL WITNESS NOTES IN THE IONIA COUNTY SURVEYORS COPY OF THE G.L.O. NOTES FOUND ON PAGE 453. CRAWFORD'S WITNESSES FOR 1891 READ " 2" RED OAK N 50° W 62 LINKS AND A 2" WHITE OAK SOUTHEAST 70 LINKS." CRAWFORD'S 1916 WITNESSES READ " 12" BLACK OAK N 47° W 39.8 FEET; POWER POLE S 49° W 63.35 FEET; HUB AND MARKER N 49° E 40.70 FEET; AND HUB AND MARKER S 49° E 26.38 FEET.

THE IONIA COUNTY ROAD COMMISSION HAS WITNESSES FOR H-3 FOUND IN THE IONIA COUNTY WITNESSES INDEX SHEETS. THE ROAD COMMISSION CALLS FOR A 1 1/4" IRON WITNESSED BY A: TELEPHONE POLE NORTHWEST 40.00 FEET; LOT IRON NORTHWEST 44.60 FEET; LOT IRON SOUTHWEST 47.50 FEET; SIGN POST SOUTHEAST 29.80 FEET (1959). D.C. CRAWFORD PLATTED LAKEVIEW PARK - LONG LAKE, SEPTEMBER 1906. CRAWFORD HAS A DISTANCE TIE TO H-3 BUT DOES NOT HAVE ANY INFORMATION ABOUT THE CORNER.

REGISTERED SURVEYOR JOHN MERDZINSKI NO. 10697 RECORDED H-3 APRIL 1976, FOUND IN LIBER 1 PAGE 173 OF ACT 74 RECORDINGS. MERDZINSKI FOUND A 1" SHAFT WITNESSED BY A: TELEPHONE POLE N 60° W 66.85 FEET; STOP SIGN N 15° E 81.65 FEET; STREET SIGN S 50° E 36.70 FEET; POWER POLE S 45° W 73.50 FEET.

B. = Description of corner evidence found and/or method applied in restoring or reestablishing corner:

FOUND 1" SHAFT AS CALLED FOR BY MERDZINSKI BEING THE SAME IRON WHICH THE ROAD COMMISSION CALLED FOR. EXCAVATED BELOW THE IRON AND FOUND A LARGE STONE. NO WITNESSES FROM 1916 REMAIN. ACCEPTED THE IRON AND STONE AS THE PERPETUATED CORNER.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

REMOVED IRON AND STONE AND SET A 30" LONG ALUMINUM MONUMENT WITH A 4" DIAMETER CAP, STAMPED "IONIA COUNTY 25863"

WITNESSED BY:

NAIL AND TAG SOUTH SIDE TELEPHONE POLE N 58° W 66.19 FEET.
NAIL AND TAG WEST SIDE WOOD POST S 27° E 54.48 FEET.
NAIL AND TAG NORTHWEST SIDE POWER POLE S 47° W 73.20 FEET
CENTERLINE ROAD SIGN POST S 50° E 37.52 FEET.

MABINUS A.

MULDER
LAND
LAND
Wo.

25863

MARINUS A. A.

Marinus A.

P.A. 345 Ionia Coun.:

Date 11-13-26

Marinus A. Mulder, Chairman

Signed by mul a mulla

Πate