SURVEY & REMONUMENTATION

FEB 15 2001

SECTION

056 2000

STATE OF MICHIGAN
IOSCO COUNTY
FILED
30 NOV 2000 2:10:31 PM
BONITA M. COYLE
REGISTER OF DEEDS

Register of Deeds Stamp & File Number

IOSCO COUNTY REMONUMENTATION
LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Iosco (County) Located In: Corner Code #

1. Public Land Survey T 21N R 6E M-5
   T 21N R 7E A-5 ✓
   T ___ R ___
   T ___ R ___
2. Property Controlling S___ T___ R___
   in Section S___ T___ R___
3. Miscellaneous S___ T___ R___
   Property in Sec. S___ T___ R___

4. Lot No. _____ , Recorded Plat _____

5. Private Claims _____

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2		6		5		4		3		2		1	
3													
4		7		8		9		10		11		12	
5													
6		18		17		16		15		14		13	
7													
8		19		20		21		22		23		24	
9													
10		30		29		28		27		26		25	
11													
12		31		32		33		34		35		36	
13													

I, JAMES H. GRANGER, in a field survey on November, 19 99 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

1837 GLO	Set Wood Post	
Lewis Clawson	12" W. Pine	S35°W 8lks
	20" W. Pine	N70°W 25lks

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Measured distance & established Township line from SE cor. Sec. 13 to NE cor. Sec. 12. Established SE cor. Sec. 12 halfway and on-line. No original evidence found. Accepted position as determined by single proportionate measurement from SE cor. Sec. 13 to NE cor. Sec. 12.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

5/8" x 30" rebar w/ Remon Cap

4" Red Maple	North	36.80" nail & tag 16041
6" Dbl. Red Maple	N30°W	35.61' nail & cap 16041
10" W. Birch	N35°E	45.60' nail & cap 16041
6" Red Maple	S18°E	19.80' nail & cap 16041
Concrete monument	S58°E	10.29'

Replaces LCRC filed as L 99 - P 48

ACCEPTED BY THE IOSCO COUNTY SURVEY PEER GROUP AS THE OFFICIAL CORNER UNDER P.A. 345 OF 1990 AT A MEETING HELD ON 10-13-99

James H Granger

STATE OF MICHIGAN
JAMES H. GRANGER
PROFESSIONAL SURVEYOR
No. 16041
LICENSED PROFESSIONAL SURVEYOR

Signed by James H Granger Date NOV. 29, 2000

Surveyor's Michigan License No. 16041

FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 1971
REVISED MAY 14,1975
REVISED JAN., 1983
REVISED OCT., 1995