

70200

# LAND CORNER RECORDATION CERTIFICATE

## FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF--:	LOCATED IN--:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY _____	T. <u>21</u> <sup>N.</sup> <del>S.</del> , R. <u>7</u> <sup>E.</sup> <del>W.</del>	<u>C-13, D-13, E-13</u>
2. PROPERTY CONTROLLING IN SECTION _____	, T. _____, S., R. _____, E. _____, W. _____	_____
3. MISCELLANEOUS PROPERTY IN SECTION _____	, T. _____, S., R. _____, E. _____, W. _____	_____
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

REGISTER OF DEEDS STAMP AND  
FILING NUMBER

I, Kenneth J. Ostling do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above (identified with circles on index code diagram—over) were, in a field survey on 2-13 1973, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on \_\_\_\_\_ 19\_\_\_\_, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

- C-13** Found 3"x3" Sq. Pine root as described in old survey notes from Arenac Co. Courthouse. Dated 1908. W.P. Stps. in place for NW OBT & SW NBT (1908)
- D-13** Found 5"x5" Square Cedar Post scribed "1/4 S T21N7E S 32" W.P. stp. in place for NW OBT showing scar but no definite face.
- E-13** Set corner from what we conclude to be the probable NBT from 1908 survey of county line. Fits measurement to corners East and West.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

C-13	D-13	E-13
D.N.R. Monument	D. N. R. Monument	Set DNR Mon.
6" Balsam      N72E    15.3	13" Bl. Ash    N11E    5.85'	12" TW S Maple    N45W    28.2
6" Birch        N43E    4.8	5" Bl. Ash     N68E    14.95'	27" W. Pine        S10E    33.9
9" Balsam      N76W    16.7		7" W. Birch        N15E    17.4'


SIGNED BY Kenneth J. Ostling DATE \_\_\_\_\_

SURVEYOR'S MICHIGAN REGISTRATION NO. 10068

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY \_\_\_\_\_ DATE \_\_\_\_\_  
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY \_\_\_\_\_ DATE \_\_\_\_\_  
MICHIGAN REGISTERED LAND SURVEYOR



(SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. \_\_\_\_\_