## SURVEY & REMONUMENTATION

APR 27 1995

For corners in

4. Lot No.

5. Private Claims \_

## COMMISSION

## IOSCO COUNTY REMONUMENTATION CORNER LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

STATE OF MICHIGAN IOSCO COUNTY FILED

Iosco (County)	Located In:	Corner Code ≠	
Public Land Survey	T 22N R 8E	К - 7	
•	T R		

5 DEC 94 1:57 P.M.

BONITA N. COYLE REGISTER OF DEEDS

94-29


Register of Deeds Stamp & File Number

2. Property Controlling in Section S \_\_\_\_ T \_\_\_ R \_ 3. Miscellaneous S \_\_\_\_ R \_ Property in Sec.

\_ , Recorded Plat \_

James H. Granger in a field survey on September do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.



A. Description of original monument and accessories and/or subsequent restoration:

1843 Original Survey

Set Wood Post

1979 Survey

1" Pipe

John Mullett

14" W. Pine N36°E 36 1ks 8" W. Birch S71°W 44 1ks

1988 Survey

Monument

1931 MDOT

Wood Stake

1936 Sub'd

Pine Ridge

1949 Sub'd

Crocker's Deer Park

1962 MDOT

US-23 road plans

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found 1" pipe. Position checks with previous survey and sub'd ties. Accepted position as established.

ACCEPTED BY THE IOSCO COUNTY SURVEY PEER GROUP AS THE OFFICIAL CORNER UNDER P.A. 345 OF 1990 AT A MEETING HELD ON 1/-10-94.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner

Set 5/8" x 30" rebar inside 1" pipe with alum cap 63.73' Set tag in Power Pole 16.42' Set tag in 20" white N70°W Set tag in 20" white pine S20°W 16.42' 53.24' Set tag in 12" cedar S50°E

67.97' Set tag in 10" twin maple N80°E



Surveyor's Michigan License No.

1994 November 10,

Date