

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in
Iron

	Located In:	Corner Code #
1. Public Land Survey	T <u>41N</u> R <u>31W</u>	<u>B1</u>
	T _____ R _____	<u>C3</u>
	T _____ R _____	
	T _____ R _____	
2. Property Controlling in Section	S <u>6</u> T _____ R _____	<u>14</u>
	S _____ T _____ R _____	
3. Miscellaneous Property in Sec.	S _____ T _____ R _____	
	S _____ T _____ R _____	

Register of Deeds Stamp & File Number

4. Lot No _____, Recorded Plat _____
 5. Private Claims _____

I, Keith Sackett, in a field survey on See below, 19____, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law, established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
2													
3													
4													
5													
6													
7													
8													
9													
10													
11													
12													
13													

A. Description of original monument and accessories and/or subsequent restoration:

<u>B1</u>	<u>C3</u>	<u>14</u>
Original monument and accessories not found.	Original monument and accessories not found. Found Wisconsin - Michigan Power Co. monument.	Not set on original survey nor subsequently, apparently.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

<u>B1</u>	<u>C3</u>	<u>14</u>
11-10-87	10-14-87	10-14-87
Restored by proportion on line.	Restored at MI-MI Power Co. monument.	Established monument on line.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

<u>B1</u>	<u>C3</u>	<u>14</u>
8ut 1" I.D. x 32" I.P. w/4" aluminum cap.		8ut 1" I.D. x 36" I.P. w/4" aluminum cap.
6" maple 804E 12.7' 1/4s NBT	16" spruce N23E 11.7' 8S NBT	4" sugar N85E 1.3' 1/16s BT
5" maple 879W 15.6' 1/4s NBT	3" spruce 839W 6.9' 67 NBT	6" sugar N08W 2.5' 1/16s BT
4" maple N33E 7.8' 1/4s NBT	8" tanerack 856E 35.0' 88 NBT	5" sugar 875W 2.5' 1/16s BT



Signed by Keith Sackett Date 2-26-88

Surveyor's Michigan License No. 18006