LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

For corners in		Filing Requiremen	t of Act 74, Mich. P.A. 1970	
	Iron (County)	Located In:	Corner Code ##	
	County	AiN 440		
1. 1	Public Land Survey	T 41N R 31N	- 43	
		ŢR	— <u>23</u> · ··	
		T R T R		
2 1	Property Controlling	s t T	7	
	in Section	S T R		
3. 1	Miscellaneous		Registe	er of Deeds Stamp & File Number
١	Property in Sec.	S T R		or Description Programmer
4. 1	Lot No R	ecorded Plat		
			2	├ ┇╌╋╌┇╼╂╾┇╼╀╾┇╌╂┈┇╶┼┈┆╺╴
ı Kı	ith Sectatt	in a field survey onBee below		
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned				
		conformance with regulations and rules ictions of the United States Department of		- - - - - - - - - - - - - - -
		Court of Law and/or that the corner point		
above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a			Surveyors or by a Decree of a	- 1 0 20 21 22 23 23
	l of Law; established, re essed below:	e-established, monumented, re-monum	ented, recovered, found as	
		orners, all in the same town and ran	· · [30 29 28 27 27 26 25 3
1101	on this certificate.	miers, an in the senie town and ran	ge, may be recorded	
			ıs	
A. I		nonument and accessories and/or su	• • • • • • • • • • • • • • • • • • • •	_
8-1-	AB	Ci Detained proposed and	C2	7 Selected assument and
	inal monument and resories not found.Found	Original monument and accessories not found. Found	Original monument and accessories not found.	Original monument and accessories not found.
	consin - Michigan Power			ECCESSOR 145 DUC TOUNG.
	ment.	sonusent.	•	
9-23	N2	ridence found and/or method applied CI 10-14-87 . • Restored at NI-MI Power Co.	d in restoring or reestablishing corr C2 10-14-87 Restored on line at proportion	ner: 7 10-14-87 Established on line at
	ment.	monument.	distance,	proportion distance.
10"	Description of monumen AB Raple \$800 14.8° B12 NB aple \$786 42.0° S6 NBT Raple \$106 24.6° S7 NBT	7° sugar N59N 4.4' \$31 MBT	shed to perpetuate locating the pos C2 Set 1° x 32° I.P. w/4° sluminum cap. 8° maple 838E 27.2° 1/4s MBT 6° sugar M26E 15.3° 1/4s MBT 5° sugar M18H 4.8° 1/4s MBT	sition of the corner:
				30 m. 1

Surveyor's Michigan License No.

APPROVER BY INICHIGAN STATE BOARD OF LAND SURVEYORS, JAN 20.
REVISED MAY 14.

2-26-98