

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Iron	Located In:	Corner Code #
<small>(County)</small>		
1. Public Land Survey	T 41N R 32W	I4
	T 41N R 32W	K2
	T _____ R _____	_____
	S _____ T _____ R _____	_____
2. Property Controlling in Section	S _____ T _____ R _____	_____
	S _____ T _____ R _____	_____
3. Miscellaneous Property in Sec.	S _____ T _____ R _____	_____
	S _____ T _____ R _____	_____

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____
 5. Private Claims

K2 Sep 19 2006
 I4 Sep 18 2006

I, Stephan J. Szyszkoski, in a field survey on _____, 20____ do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

- (I4) Quarter corner common to Sections 10 and 11. 1978 - Reestablished by single proportionate measurement to the original record by A.O. Enger RLS. Set 1" IDx36" iron pipe with 3 3/4" aluminum cap. Red Oak 13 N54E 32.3', Red Oak 9 S53E 52.0'.
- (K2) Quarter corner common to Sections 1 and 2. 1849 - Established by John Burt, Deputy Surveyor, midway and on line between Section corners 40.00 chains north and south. Set sugar post. Y. Birch 10 N34E 34 links, Y. Birch 8 S28W 25 links. Circa 1943 - Corner reestablished by Wisconsin-Michigan Power Company by unknown method but presumed to be by single proportionate measurement to the original record between Section corners. A 1947 WMPCO map shows "no evidence" found and set "concrete marker" with witnesses 16" W. Pine N42E 41.8', and 5" Poplar S48E 11.9'.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

- (I4) Recovered the 1978 monument in good condition and at record bearing and distance from the 1978 NBTs, in good condition but with no markings or blazes visible. My measurements show that the monument is located 0.13' East of the proportionate position intended in 1978 and I accept the monument as a careful and faithful reestablishment of the position of the original corner.
- (K2) The original monument and accessories were not recovered. Found the WMPCO monument of record, a 7" right-rectangular concrete pyramid with brass cap stamped to identify the corner, in good condition. The WMPCO witnesses were not recovered. My measurements show this monument is located 7.82' north and 5.03' east from the single proportionate position between Section corners K1 and K3. I accept the monument as a careful and faithful reestablishment of the position of the original corner. Made new witnesses as described below.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

- | | |
|--|--|
| (I4) Fd. 1" ID I. pipe with 3 3/4" alum. MDNR cap. Set measuring nails in: | (K2) Fd. WMPCO concrete monument. Set measuring nails in: |
| 13" Oak N58E 32.5' mrkd "1/4S NBT" * | 5" Aspen N03E 17.2' mrkd "1/4S NBT" |
| 11" Oak S49E 52.1' do * | 4" Aspen N82E 6.05' do |
| 8" Oak S39W 20.5' do | 9" Aspen S49W 23.4' do |
| 9" Oak N17W 38.0' do | 2" W. Spruce N58W 10.5' |
| Fd. sq'd cedar post adjacent. Bearings are magnetic. Distances are to nail with tag. * denotes 1978 NBT. | Set sq'd cedar post adjacent. Bearings are magnetic. Distances are to nail with tag. |



Signed by Stephan J. Szyszkoski
 Surveyor's Michigan License No. 33986

Date 9/26/06

For the Michigan Department of Natural Resources, Office of Land and Facilities