LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF -:		DCATED IN -:	í	ORNER CODE	NUMBER	i	
1. PUBLIC LAND SUE	RVEY T.	42 X. R. 3	2 X .	F 3			
2. PROPERTY CONTI	ROLL- 4	42 8 3	g K .	16			
3. MISCELLANEOUS PROPERTY IN SEC	TION	. T.T.	**	· · · · · · · · · · · · · · · · · · ·	* 1		
PROPERTY IN SEC	. F., XOIT.	S., R	W				
4. LOT NO	, RECORDE	D PLAT		_	** * **	İ	
5. PRIVATE CLAIMS			· 			REGISTER OF D	EEDS STAMP AND
. Arthur O. 1	Inger					FILING	NUMBER
restored as expresse of survey instruction court of law. Fu	d below and in s of the United rthermore, that 19, found	- 19 , esta conformance wi States Departm the corner po , recovered, resi	blished, re- th regulation ent of the li ints mention tored, establ	established, ns and rules to sterior, Burea ned in lines ished or re-es	monumente therefore as u of Land! 3, 4 and 5, stablished:	d, re-monuments required in the Management or above were, in as expressed by	ted, recovered one current manual by a decree of a a field survey of clow and in con-
taw:							
A. Description of ori							
Corner F 3:	Original mo W. Pine 8	nument not : S55W 24	specified	(not foun	d)		
	S. Pine 10		_	H #0			
	wo ampaedm	ent monument	s found.				
B. Description of cor		und and/or meth	nod applied	in restoring o	r re-establi	shing corner:	
B. Description of cor Corner F 3:	ner evidence fo Re-establish to E and to	und and/or meth ned June 28, W.	nod applied 1971 on	in restoring o	r re-establi Ben sect:	shing corner:	39.897 ch.
B. Description of cor Corner F 3: Corner 16:	ner evidence fo	und and/or methed June 28, W. August 19.	1971 on	in restoring o	r re-establi Ben sect:	shing corner:	39.897 ch.
B. Description of cor Corner F 3: Corner 16:	ner evidence fo Re-establish to E and to Betablished E and 1/4 co	und and/or method June 28, W. August 19, pr. 19.949 c	1971 on 1971 on 1971 on 1 h. W.	in restoring o	r re-establi Ben sect: Bn sectio	ishing corner: ion corners on corner 1	39.897 ch. 9.948 ch.
B. Description of cor Corner F 3: Corner 16:	ner evidence for nument for corn	und and/or method June 28, W. August 19, pr. 19.949 c	1971 on 1971 on 1971 on 1 h. W.	in restoring of line between the between shed to perpendicular to perpendi	r re-establi een sections en sections	ishing corner: ion corners on corner 1 ing the position	39.897 ch. 9.948 ch.
B. Description of cor Corner F 3: Corner 16:	ner evidence for Re-established to E and 1/4 continument for corner both corner	und and/or method June 28, W. August 19, or. 19.949 c	1971 on 1971 o	in restoring of line between shed to perper on pipe with ag.) 7.5	r re-establi een section tuate locat th 4" al ft. "1/4 ft. "1/4	ishing corner: ion corners on corner 1 ing the position uminum cap	39.897 ch. 9.948 ch.
B. Description of cor Corner 7 3: Corner 16: C. Description of mo. Honuments for	ner evidence for Re-establish to E and to Established E and 1/4 connument for corn both corner Corner F3:	und and/or method June 28, W. August 19, or. 19.949 c er and accessors: 1" I.D. J. Pine 11 J. Pine 11 Variation (1971 on 1971 on 1971 on 1h. W. ries establi x 36" ir N85°E (m N55°W (m O°15' Eas	in restoring of line between shed to perpending on pipe with ag.) 7.5 ag.) 17.8 t at this	tuate locate the "1/4 ft. "1/4 corner.	ishing corner: ion corners on corner 1 ing the position uminum cap s, NBT" s, NBT"	39.897 ch. 9.948 ch.
B. Description of cor Corner 7 3: Corner 16; C. Description of mo Monuments for Witnesses for	ner evidence for Re-establish to E and to E and to E and to E and 1/4 consument for corn both corner Corner F3:	und and/or method June 28, W. August 19, or. 19.949 c er and accessors: 1" I.D. J. Pine 11 J. Pine 11 Variation (J. Pine 6 J. Pine 4	1971 on 1971 o	in restoring of line between the between shed to perpending.) 7.5 ag.) 17.8 t at this ag.) 7.3 ag.) 5.1	tuate locate the distribution of the distribut	ishing corner: ion corners on corner 1 ing the position uminum cap s, NBT" s, NBT"	39.897 ch. 9.948 ch.
B. Description of cor Corner F 3: Corner 16: C. Description of mo Monuments for Witnesses for Witnesses for GIGNED BY	ner evidence fo Re-establish to E and to Established E and 1/4 co nument for corn both corner Corner F3: AN REGISTRA	und and/or method June 28, W. August 19, or. 19.949 c er and accessors: 1" I.D. J. Pine 11 J. Pine 11 Variation (J. Pine 4	1971 on 1971 o	in restoring of line between the between shed to perpending on pipe with ag.) 7.5 ag.) 17.8 t at this ag.) 7.3 ag.) 5.1	tuate locate the distribution of the distribut	ion corners on corner 1 ing the position cuminum cap S, NBT" S, NBT" 6S, BT"	39.897 ch. 9.948 ch.
B. Description of cor Corner F 3: Corner 16: C. Description of mo Monuments for Witnesses for Witnesses for	ner evidence fo Re-establish to E and to Betablished E and 1/4 co nument for corn both corner Corner F3: Corner 16:	und and/or method June 28, W. August 19, or. 19.949 c er and accesso s: 1" I.D. J. Pine 11 J. Pine 11 Variation (J. Pine 6 J. Pine 4	1971 on 1971 o	in restoring of line between the between shed to perpending on pipe with ag.) 7.5 ag.) 17.8 t at this ag.) 7.3 ag.) 5.1	tuate locate the distribution of the distribut	ion corners on corner 1 ing the position cuminum cap S, NBT" S, NBT" 6S, BT"	39.897 ch. 9.948 ch.
B. Description of cor Corner F 3: Corner 16: C. Description of mo Monuments for Witnesses for Witnesses for GIGNED BY	ner evidence fo Re-establish to E and to Established E and 1/4 co nument for corn both corner Corner F3: Corner 16:	wind and/or method June 28, W. August 19, or. 19.949 c er and accessors: 1" I.D. J. Pine 11 J. Pine 11 Variation (J. Pine 6 J. Pine 4	1971 on 1971 o	in restoring of line between the between shed to perpending on pipe with ag.) 7.5 ag.) 17.8 t at this ag.) 7.3 ag.) 5.1	tuate locate the distribution of the distribut	ion corners on corner 1 ing the position cuminum cap s, NBT" 6S, BT" 6S, BT"	39.897 ch. 9.948 ch.
B. Description of cor Corner F 3: Corner 16: C. Description of mo. Honuments for Witnesses for Witnesses for GURVEYOR'S MICHIG FOR STATE AND UNI	ner evidence fo Re-establish to E and to Established E and 1/4 co nument for corn both corner Corner F3: Corner 16:	wind and/or method June 28, W. August 19, or. 19.949 c er and accessors: 1" I.D. J. Pine 11 J. Pine 11 Variation (J. Pine 6 J. Pine 4	1971 on 1971 o	in restoring of line between the between shed to perpending on pipe with ag.) 7.5 ag.) 17.8 t at this ag.) 7.3 ag.) 5.1	tuate locate the distribution of the distribut	ion corners on corner 1 ing the position cuminum cap s, NBT" 6S, BT" 6S, BT"	39.897 ch. 9.948 ch.
B. Description of cor Corner F 3: Corner 16: C. Description of mo. Honuments for Witnesses for Witnesses for GIGNED BY GURVEYOR'S MICHIG FOR STATE AND UNIT	ner evidence fo Re-establish to E and to Established E and 1/4 co nument for corn both corner Corner F3: Corner 16: AN REGISTRA TED STATES A	und and/or method June 28, W. August 19, or. 19.949 c er and accesso s: 1" I.D. J. Pine 11 J. Pine 11 Variation (J. Pine 6 J. Pine 4	1971 on 1971 o	in restoring of line between the between shed to perpending on pipe with ag.) 7.5 ag.) 17.8 t at this ag.) 7.3 ag.) 5.1 DATH DATH	r re-establicen section tuate locate th 4" al ft. "1/4 ft. "1/4 corner. ft. "1/1 ft. "1/1	ion corners on corner 1 ing the position cuminum cap s, NBT" 6S, BT" 6S, BT"	39.897 ch. 9.948 ch.

· ·

FORM No. ML M735
DOUBLEDAY BROS. & CO., KALAMATOO, MICH.

FORM APPROVED BY MICHIGAN STATE BOAHD OF REGISTRATION, JAN. 28, 1-7-1 DISTRIBUTED BY MICHIGAN SOCIETY OF REGISTERED LAND SURVEYORS