## LAND CORNER RECORDATION CERTIFICATE

## FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF -:	LOCATED IN-:	CORNER CODE NUMBER	
1. PUBLIC LAND SURVEY	T. 43 %, R. 33 %	D6	
2. PROPERTY CONTROLL- 17 ING IN SECTION	T. 43 St. R. 33 W.	17-5 & 17-9	
3. MISCELLANEOUS PROPERTY IN SECTION			
4. LOT NO, RECO	ORDED PLAT		
5. PRIVATE CLAIMS			REGISTER OF DEEDS STAMP AND FILING NUMBER
Arthur 0. Enger, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on see below, 19, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on, 19, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:  A. Description of original monument and accessories and/or subsequent restoration:  Corner D 6 (Center of Section 17, T43N, R33W):  Corner 17-5 (North 1/16 corner on N & S 1/4 line of Sec. 17, T43N, R33W):  Corner 17-9 (East 1/16 corner on E & W 1/4 line of Sec. 17, T43N, R33W):  None of these corners established in original survey nor subsequently, apparently.			
<ul> <li>B. Description of corner evidence found and/or method applied in restoring or re-establishing corner;</li> <li>Corner D6: Established 7/29/75 at intersection of quarter-section lines.</li> <li>Corner 17-5: Established 7/30/75 on true N &amp; S 1/4 line between Center 1/4 cor.</li> <li>20.138 ch. S and N 1/4 cor. 20.138 ch. N.</li> <li>Corner 17-9: Established 7/30/75 on true E &amp; W 1/4 line between Center 1/4 cor. 20.105 ch. W and E 1/4 cor. 20.105 ch. E.</li> </ul>			
C. Description of monument for	corner and accessories establish	ned to perpetuate locating th	e position of the corner:
Monuments for all 3 co Witnesses for Corner D	6: W. Pine 16 N6 <sup>O</sup> W	(mag.) 41.4 ft. "1/	/4S, BT"
Witnesses for Corner 1	7-5: Tamarack 6 N85 <sup>O</sup> W Cedar 8 S20 <sup>O</sup> E	(mag.) 38.0 ft. "1/	/16S, BT" /16S, BT"
	S. Maple 4 N18 W	(mag.) 10.5 ft. "1/	/16S, BT"
SIGNED BY		DATE	
SURVEYOR'S MICHIGAN REG	ISTRATION NO		(SEAL)
FOR STATE AND UNITED ST	ATES AGENCIES:		
SIGNED BY	CHIEF OF SURVEY PARTY)	DATE	November 22, 11976
APPROVED AND SIGNED BY_		r	November 22,71976
SURVEYOR'S MICHIGAN REGISTRATION NO. 13581  FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 26, 1971 REVISED MAY 14, 1373			

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET