

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in
 T & R

County	Located in:	Corner Code -#
1. Public Land Survey	T 44N R31W	
	T R	
	T R	
	T R	
2. Property Controlling in Section	S 1 T R	3
	S 12 T R	10
3. Miscellaneous Property in Sec.	S 17 T R	16
	S T R	

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____
 5. Private Claims _____

I, Karl Sackett, in a field survey on January 9, 19 89, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

3	10	16
Not set on original survey nor subsequently, apparently.	Not set on original survey nor subsequently, apparently.	Not set on original survey nor subsequently, apparently.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

3	10	16
Established midway and on line.	Established midway and on line.	Established midway and on line.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

3	10	16
Set 1" 18 x 32" IP w/4" aluminum cap.	Set 1" 18 x 32" IP w/4" aluminum cap.	Set 1" x 34" IP w/4" aluminum cap.
14" cedar N80E 17.0' 1/16s BT with Champion location poster.	8" balsam N66W 9.7' 1/16s BT	8" maple N41W 56.9' 1/16s BT
32" cedar S45E 18.6' 1/16s BT	10" balsam S69W 9.9' 1/16s BT	10" maple S31W 81.6' 1/16s BT
12" cedar West 31.4' 1/16s BT	4" spruce N65E 21.5' 1/16s BT	12" white pine N64E 119.6' 1/16s BT

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	1	2	3	4	5	6	7	8	9	10	11	12	13
3	14	15	16	17	18	19	20	21	22	23	24	25	26
4	27	28	29	30	31	32	33	34	35	36	37	38	39
5	40	41	42	43	44	45	46	47	48	49	50	51	52
6	53	54	55	56	57	58	59	60	61	62	63	64	65
7	66	67	68	69	70	71	72	73	74	75	76	77	78
8	79	80	81	82	83	84	85	86	87	88	89	90	91
9	92	93	94	95	96	97	98	99	100	101	102	103	104
10	105	106	107	108	109	110	111	112	113	114	115	116	117
11	118	119	120	121	122	123	124	125	126	127	128	129	130
12	131	132	133	134	135	136	137	138	139	140	141	142	143
13	144	145	146	147	148	149	150	151	152	153	154	155	156

Signed by Karl Sackett Date 1-19-89

Surveyor's Michigan License No. _____ 19000

