

**LAND CORNER RECORDATION CERTIFICATE**  
**Filing Requirement of Act 74, Mich. P.A. 1970**

For corners in Iron	Located In:	Corner Code -#
(County)		
1. Public Land Survey	T 44N R 32W	16
	T R	JS
	T R	
	T R	
2. Property Controlling in Section	S 14 T R	3
	S T R	10
3. Miscellaneous Property in Sec.	S T R	
	S T R	

Register of Deeds Stamp & File Number

4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_  
 5. Private Claims \_\_\_\_\_

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2	1							
3													
4	7	6	5	4	3	2	1						
5													
6	8	7	6	5	4	3	2	1					
7													
8	9	8	7	6	5	4	3	2	1				
9													
10	10	9	8	7	6	5	4	3	2	1			
11													
12	11	10	9	8	7	6	5	4	3	2	1		
13													

I, Keith Sockell, in a field survey on June 14, 1988, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

16	JS	3	10
Original monument and accessories not found.	Original monument and accessories not found.	Not set on original survey not subsequently, apparently.	Not set on original survey not subsequently, apparently.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

16	JS	3	10
Restored midway and on line.	Restored midway and on line.	Established midway and on line.	Established midway and on line.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

16	JS	3	10
Set 1" ID x 3/8" IP with 4" aluminum cap.	Set 6-14-89 1" I.D. x 3/2" I.P. with 4" aluminum cap.	Set 1" ID x 3/8" IP with 4" aluminum cap.	Set 1" ID x 3/8" IP with 4" aluminum cap.
4" white pine S82E 4.7' 1/4S, NDT	8" spruce S24W 1.3' 1/4S NDT	12" white pine S70E 1/16S, BT	16" cedar N15E 40.3' 1/16S, BT
3" tamarack N84W 17.1' 1/4S, NDT	7" spruce S82E 7.0' 1/4S NDT	4" spruce S5.2' S11N 1/16S, BT	12" cedar S82W 32.0' 1/16S, BT
2" tamarack N02E 14.8' 1/4S, NDT	6" spruce N24W 8.2' 1/4S NDT	4" spruce S7.4' N63W 1/16S, BT	5" balsam S71E 5.7' 1/16S, BT

Signed by Keith Sockell Date \_\_\_\_\_

Surveyor's Michigan License No. \_\_\_\_\_ 19006

