

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

IRON COUNTY

FOR CORNERS OF--:	LOCATED IN--:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY. _____	T. <u>44</u> N. R. <u>33</u> W.	H3, G2
2. PROPERTY CONTROLLING IN SECTION. _____	T. _____ N. S. R. _____ E. W.	G1, G3
3. MISCELLANEOUS PROPERTY IN SECTION. _____	T. _____ N. S. R. _____ E. W.	
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Keith L. Sackett, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on 4-19-84, 1984, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

- A. Description of original monument and accessories and/or subsequent restoration:
- Corner H3: Original monument and accessories not found.
 - Corner G2: Original monument and accessories not found.
 - Corner G1: Found old L.L.S. and rebar as corner recorded by Gary Pason.
 - Corner G3: Found rebar set by Bob Perkins.

- B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:
- Corner H3: Restored 3-26-84 midway and on line between corners east and west.
 - Corner G2: Restored 4-19-84 by proportion between corners north and south.
 - Corner G1: Restored 4-19-84.
 - Corner G3: Restored 4-19-84.

- C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:
- Corner H3: Set 1" I.D. by 32" iron pipe with 4" alum. cap.
7" maple S86W 30.6 ft 1/4s, NBF
7" spruce S50E 29.2 ft 1/4s, NBF
 - Corner G2: Set 1" I.D. by 32" I.P. with 4" alum. cap.
10" spruce N62W 66.7 ft 1/4s, NBF
 - Corner G1 & G3: Set 1" I.D. by 32" I.P. with 4" alum. cap.

SIGNED BY _____ DATE _____

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____

APPROVED AND SIGNED BY Keith L. Sackett DATE 8-17-84

CHIEF OF SURVEY PARTY
Keith L. Sackett
 MICHIGAN REGISTERED LAND SURVEYOR
 Michigan Department of Natural Resources

SURVEYOR'S MICHIGAN REGISTRATION NO. 19006

