

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Iron	Located In:	Corner Code #:
(County)		
1 Public Land Survey	T 45N R 11W	J 11
	T R	
	T R	
	T R	
2 Property Controlling	S 26 T R	10
in Section	S 35 T R	1
3 Miscellaneous	S T R	3
Property in Sec	S T R	

Register of Deeds Stamp & File Number

4 Lot No _____, Recorded Plat _____
 5 Private Claims _____

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	16	17	18	19	20	21	22	23	24				
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

I, Keith Sabbatt, in a field survey on June 15, 1988, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law, established, re-established, monumented, re-monumented, recovered, found as expressed below.

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A Description of original monument and accessories and/or subsequent restoration:

J 11	10	1	3
Original monument and accessories not found.	Not set on original survey nor subsequently, apparently.	Not set on original survey nor subsequently, apparently.	Not set on original survey nor subsequently, apparently.

B Description of corner evidence found and/or method applied in restoring or reestablishing corner:

J 11	10	1	3
Restored midway on line.	Established midway on line.	Established midway on line.	Established midway on line.

C Description of monument for corner and accessories established to perpetuate locating the position of the corner.

J 11	10	1	3
Set 1"x36" I.P. with 4" aluminum cap.	Set 1"x36" I.P. with 4" aluminum cap.	Set 1"x36" I.P. with 4" aluminum cap.	Set 1"x36" I.P. with plastic plug DNR RLS-19006
4" maple S89E 2.9' 1/4sNBT	4" spruce S34W 12.1' 1/16s BT	6" spruce S17E 8.8' 1/16s BT	8" spruce S46W 16.1' 1/16s BT
5" red pine N10W 11.4' 1/4sNBT	5" spruce N73W 7.4' 1/16s BT	6" spruce N04E 9.8' 1/16s BT	10" spruce N34W 17.0' 1/16s BT
4" spruce S59W 9.1' 1/4sNBT	12" spruce N42E 26.6' 1/16s BT	6" spruce N36W 8.1' 1/16s BT	8" spruce S67E 41.9' 1/16s BT

Signed by Keith Sabbatt Date December 9, 1988

Surveyor's Michigan License No. _____ 19006