LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

| For | corners | in | |
|-----|---------|----|--|
| | lron | | |

Located In: Corner Code ≠#

T_45N_ R 31H ... 1. Public Land Survey 2. Property Controlling

in Section 3. Miscellaneous Property in Sec.

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat

5. Private Claims

I. <u>Keith Sackett</u>, in a field survey on <u>June 22</u>, 19 <u>88</u>, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law, established, re-established, monumented, re-monumented, recovered, found as expressed below.

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

110

Original monument and accessories not found.

Not set on original survey nor subsequently, apparently.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

110

Restored midway on line.

Established midway on line.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Set 1"x32" E.P. w/4" miuminum Set 1"1.8 x 32" I.P. w/4" alweinum cap.

7" w.birch \$85E 11.9" 1/45 MBT 6" sugar MOZE 21.1 1/168 BT

3° sugar SOIN 7.7' 1/48 NBT 4° sugar NO7M 2.8' 1/49 NBT

7" sugar BOSE 14.4" 1/165 BT 6" sugar 873N 29.9" 1/168 BT

Surveyor's Michigan License No.