IRON Co

# LAND CORNER RECORDATION CERTIFICATE

## FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

| FOR CORNERS OF—: | LOCATED IN—: | CORNER CODE NUMBER |
|---|---|---|
| 1. PUBLIC LAND SURVEY | T. 45 N. S., R. 32 E. W. | C4, C3 |
| 2. PROPERTY CONTROLLING IN SECTION 8 | T. 45 N. S., R. 32 E. W. | 3, 10 |
| 3. MISCELLANEOUS PROPERTY IN SECTION | T. N. S., R. E. W. | |

4. LOT NO. _____, RECORDED PLAT _____

5. PRIVATE CLAIMS _____

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Keith Sackett, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on 3-28, 1984, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

Corner C4: Original monument and accessories not found.

Corner C3: Original monument and accessories not found. Found Northern Paper Mills Monument set by Buce Bueil

Corner 3: Not set on original survey nor subsequently apparently.

Corner 10: Not set on original survey nor subsequently apparently.

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

Corner C4: Restored Midway and on line between corners North and South.

Corner C3: Restored at Northern Paper Mills Monument

Corner 3: Established Midway and on Line between section corner North and ¼ corner South.

Corner 10: Established Midway and on Line between section corner south and ¼ corner North.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Corner C4: Set 1" I.D. by 32" Iron Pipe with 4" alum. cap.
16" cedar N08E 47.1 Ft. ¼S, NBT
7" tamarack S64E 34.7 Ft. ¼S, NBT

Corner 3: Set 1" I.D. by 32"I.P. with 4" alum. cap.
6" spruce N47E 24.2 Ft. 1/16S, BT
7" B. Ash S55W 42.2 Ft. 1/16S, BT

Corner C3: Northern Paper Mills Monument
7" balsm S89W 8.5 Ft. S7,NBT
8" balsm N16W 15.9 Ft. S6, NBT
6" balsm S50E 14.9 Ft. S8, NBT

Corner 10: Set 1" I.D. by 32" I.P. with 4" alum. cap.
4" spruce N20E 18.5 Ft. 1/16S, BT
7" tamarack N42W 26.5 Ft. 1/16S, BT
8" spruce S18E 43.0 Ft. 1/16S, BT
3" spruce squared S54W 3.5 Ft.

SIGNED BY _____ DATE _____

SURVEYOR'S MICHIGAN REGISTRATION NO. _____ (SEAL)

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____

APPROVED AND SIGNED BY Keith L. Sackett (CHIEF OF SURVEY PARTY / MICHIGAN REGISTERED LAND SURVEYOR) DATE 8-7-8

Keith L. Sackett
Michigan Department of Natural Resources

(SEAL) STATE OF MICHIGAN KEITH L SACKETT LAND SURVEYOR NO. 19006 REGISTERED LAND SURVEYOR

SURVEYOR'S MICHIGAN REGISTRATION NO. 19006

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
REVISED MAY 14, 1975

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET