LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

IRON COUNTY

FOR CORNERS OF—:	LOCATED IN—:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY	T. 45 N. S., R. 32 E. W.	E9, E6, E7
2. PROPERTY CONTROLLING IN SECTION	,T. N. S., R. E. W.	
3. MISCELLANEOUS PROPERTY IN SECTION	,T. N. S., R. E. W.	
4. LOT NO. , RECORDED PLAT		
5. PRIVATE CLAIMS		

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Keith L. Sackett, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on 5-9-83, 19____, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on_____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

Corner E9: Original monument and accessories not found. Found old squared post down and rotted. Found old Northern Paper Mill's location poster.

Corner E6: Original monument and accessories not found.

Corner E7: Original monument and accessories not found. Found Northern Paper Mill's location poster on 18" Sugar S62W 44.0 ft.

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

Corner E9: Restored at old wood post.
Fits good with other corners in area.

Corner E6: Restored midway and on line between corners north and south.

Corner E7: Restored by double proportion between corners and land calls.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Corner E9: Set 1" I.D. by 32" I.P. w/4" alum. cap.
9" Sugar S82E 15.8 ft S28, NBT
5" Sugar N06W 22.3 ft. S20, NBT
10" Sugar S45W 17.6 ft. S29, NBT
6" Iron wood squared west 3.0 ft.

Corner E6: Set 1" I.D. by 32" I.P. w/4' alum. cap.
9" Spruce S54W 18.9 ft 1/4S NBT
6" Spruce N35E 44.4 ft 1/4S, NBT

Corner E7: Set 1" I.D. by 32" I.P. w/4" alum. cap
7" Sugar N17W 3.4 ft S17, NBT
5" Sugar N69E 13.8 ft S16, NBT
7" Sugar S22W 11.5 ft. S20, NBT

SIGNED BY_____ DATE_____

SURVEYOR'S MICHIGAN REGISTRATION NO._____ (SEAL)

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY_____ CHIEF OF SURVEY PARTY DATE_____

APPROVED AND SIGNED BY Keith L. Sackett MICHIGAN REGISTERED LAND SURVEYOR DATE 6-29-83

(SEAL) STATE OF MICHIGAN 19006 REGISTERED LAND SURVEYOR

SURVEYOR'S MICHIGAN REGISTRATION NO. 19006

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
REVISED MAY 14, 1975

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET