

# LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A. 1970

IRON COUNTY

FOR CORNERS OF--	LOCATED IN--	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY	T. _____ N. _____ S. _____ R. _____ E. _____ W. _____	
2. PROPERTY CONTROLLING IN SECTION	20 T. 45 N. _____ S. _____ R. 32 E. _____ W. _____	1, 2
3. MISCELLANEOUS PROPERTY IN SECTION	T. _____ N. _____ S. _____ R. _____ E. _____ W. _____	
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

REGISTER OF DEEDS STAMP AND  
FILING NUMBER

I, Keith L. Sackett, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on see below, 19\_\_\_\_, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on \_\_\_\_\_, 19\_\_\_\_, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

**A. Description of original monument and accessories and/or subsequent restoration:**

Corner 1: Not set on original survey nor subsequently apparently.

Corner 2: Not set on original survey nor subsequently apparently.

**B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:**

Corner 1: Established 10-11-83 midway and on line between corners east and west.  
Corner 2: Established 10-28-83 midway and on line between corners east and west.

**C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:**

Corner 1: Set 1" ID by 36" I.P. w/4" alum. cap.  
5" Tamarack S30W 24.4 ft. 1/16S, BT  
4" Tamarack S46E 11.8 ft. 1/16S, BT  
2" Tamarack N63E 10.8 ft. 1/16S, BT  
Corner 2: Set 1" I.D. by 32" I.P. w/4" alum. cap.  
14" W. birch N86E 26.4 ft. 1/16S, BT  
12" Spruce N45W 30.9 ft. 1/16S, BT  
8" W. birch S73W 46.2 ft. 1/16S, BT

SIGNED BY \_\_\_\_\_ DATE \_\_\_\_\_

SURVEYOR'S MICHIGAN REGISTRATION NO. \_\_\_\_\_ (SEAL)

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY \_\_\_\_\_ DATE \_\_\_\_\_

APPROVED AND SIGNED BY Keith L. Sackett DATE 11-28-83  
CHIEF OF SURVEY PARTY  
MICHIGAN REGISTERED LAND SURVEYOR

Keith L. Sackett  
Michigan Department of Natural Resources

SURVEYOR'S MICHIGAN REGISTRATION NO. 19006

