

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in
Iron
 (County)

Located In: _____ Corner Code # _____

- | | | | |
|------------------------------------|------|-------------|-------|
| 1. Public Land Survey | T | R | _____ |
| | T | R | _____ |
| | T | R | _____ |
| | T | R | _____ |
| 2. Property Controlling in Section | S 36 | T 45N R 32W | 10 |
| | S 36 | T 45N R 32W | 11 |
| 3. Miscellaneous Property in Sec. | S | T | R |
| | S | T | R |

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____
 5. Private Claims _____

11 Apr 02 2003
 10 May 05 2003

I, Stephan J. Szyszkoski, in a field survey on _____, 20____ do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2				
3													
4	7		8		9		10		11				
5													
6	18		17		16		15		14				
7													
8	19		20		21		22		23				
9													
10	30		29		28		27		26				
11													
12	31		32		33		34		35				
13													

- A. Description of original monument and accessories and/or subsequent restoration:
 (10-Sec. 36) South 1/16 corner between Sections 35 and 36. Not established in the original survey. Found no subsequent record.
 (11-Sec. 36) Southwest 1/16 corner, Section 36. Not established in the original survey. Found no subsequent record.

- B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:
 (10-Sec. 36) Established the corner midway and on a straight line between Section corner 1293.07' south and Quarter corner 1293.07' north.
 (11-Sec. 36) Established the corner at the intersection of straight lines connecting opposite 1/16 corners.

- C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:
 (10) Set a 1"IDx32" I.pipe with 4" alum MDNR cap driven into broken rock and made firm with a mound of rock. Blazed, scribed, and set meas. nails in:
 6" Sugar N80E 30.9' "1/16S BT"
 9" Sugar S01E 23.4' do
 6" Sugar West 16.7' do
 7" Sugar N04W 31.7' do
 Bearings are magnetic. Distances are to nail with tag.
 (11) Set 1"IDx36" I.pipe with 4" alum. MDNR cap. Blazed, scribed, and set measuring nails in:
 9" dbl Y.Birch N19E 0.6' "1/16S BT"
 5" Spruce S05W 3.2' do
 12" Cedar S49W 47.6' do
 12" Hemlock N55W 34.5' do
 Bearings are magnetic. Distances are to nail with tag.



Signed by Stephan J. Szyszkoski
 Surveyor's Michigan License No. 33986

Date 5/29/03