LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

Iron County

FOR CORNERS OF—:	LOCATED IN—:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY	T. 46 N. S., R. 33 E. W.	G11, F11
2. PROPERTY CONTROLLING IN SECTION 28	T. 46 N. S., R. 33 E. W.	15
3. MISCELLANEOUS PROPERTY IN SECTION	T. N. S., R. E. W.	

4. LOT NO. _____, RECORDED PLAT _____

5. PRIVATE CLAIMS _____

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Keith L. Sackett, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on 6-5-85, 19__, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19__, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

Corner G11: Original monument and accessories not found. Found old tag by unknown person. Old blazed and paint lines.

Corner F11: Original monument and accessories not found.

Corner 15: Not set on original survey nor subsequently apparently.

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

Corner G11: Restored at old used location. Fits good by double proportion.

Corner F11: Restored midway and on line between corners east and west.

Corner 15: Established midway and on line between corners east and west.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner.

Corner G11:	Set 1" I.D. by 32" I.P. with 4" alum. cap.	10" sugar	S02W	13.6'	S33, NBT
		9" sugar	N50W	5.2'	S28, NBT
		16" sugar	S48E	19.1'	S34, NBT
Corner F11:	Set 1" I.D. by 32" I.P. with 4" alum cap.	4" Tamarack	N74W	40.0'	¼S, NBT
		10" Tamarack	S30W	35.5'	¼S, NBT
Corner 15:	Set 1" I.D. by 32" I.P. with 4" alum. cap.	24" Spruce	N58W	3.5'	1/16S, BT
		8" Cherry	S60E	12.4'	1/16S, BT
		5" Spruce	S20W	19.1'	1/16S, BT

SIGNED BY _____ DATE _____

SURVEYOR'S MICHIGAN REGISTRATION NO. _____ (SEAL)

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY Michael W. Rope (CHIEF OF SURVEY PARTY) DATE 6-5-85

APPROVED AND SIGNED BY Keith L. Sackett (MICHIGAN REGISTERED LAND SURVEYOR) DATE 6-5-85 (SEAL)

Keith L. Sackett
Department of Natural Resources

SURVEYOR'S MICHIGAN REGISTRATION NO. 19006

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
REVISED MAY 14, 1975

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET