TACKSON

LAND CORNER RECORDATION CERTIFICATE FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

| FOR CORNERS OF -: | LOCATED IN -: | CORNER CODE NUMBER | |
|---|-----------------------|--------------------|---|
| 1. PUBLIC LAND SURVEY_6 | T | <u> </u> | |
| 2. PROPERTY CONTROLL- 6 | ,T S., R E. | C-3 | |
| 3. MISCELLANEOUS PROPERTY IN SECTION | N. S., R E. | | |
| 4. LOT NO, RECO | RDED PLAT | | |
| 5. PRIVATE CLAIMS | | | REGISTER OF DEEDS STAMP AND FILING NUMBER |
| do hereby certify that under requirements of P.A.74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above (identified with circles on index code diagram – over) were, in a field survey on Oct. 2 1923, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on Oct 12 1923, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law: | | | |
| A. Description of original monument and accessories and/or subsequent restoration: | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| B. Description of corner evidence found and/or method applied in restoring or re-establishing corner: | | | |
| FOUND POINTED STONE with to IRON PIPE by it IN old FERRE COR. | | | |
| RECOVERED WITHNOTES OF A SURVEY MADE by CONSTRUER POWER CO | | | |
| JACKSON, MICHIGAN IN 1966 | | | |
| | | | |
| C. Description of monument for corner and accessories established to perpetuate locating the position of the corner: | | | |
| PointEd StonE wi | in 15" IRON Pipe by | int a second | |
| North 93.2 | 0' 24" BASS | · waad | |
| N. 81° F. 19.2 | 0' 24"B.Ch. | (RRY (Twin) | |
| N. 81° E. 18.79 S 31° W 16.98 | 0' 3" W. As. | h | |
| | · | | |
| SIGNED BY | | DATE | |
| SURVEYOR'S MICHIGAN REGISTRATION NO. 12029 (SEAL) | | | |
| FOR STATE AND UNITED STA | | | |
| SIGNED BY | CHIEF OF SURVEY PARTY | DATE | . |
| APPROVED AND SIGNED BY MICHIGAN REGISTERED LAND SURVEYOR | | | |
| | MINTER REPORTERED LAN | | (SEAL) |
| | | | |

SURVEYOR'S MICHIGAN REGISTRATION NO. _

Form No. ML M735
DOUBLEDAY BROS. & CO., KALAMAZOO, MICH.

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971 DISTRIBUTED BY MICHIGAN SOCIETY OF REGISTERED LAND SURVEYORS