Surveyor's Michigan License No. _

28409

JACKSON COUNTY APPROVED LAND CORNER P.A. 345 of 1990 Chairman Language Date Dec. 20,1994	E 🕹 CORNER TOMPKINS	ER SECTION ZO SECTION 27 TOWNSHIP ORDATION CERTIFICAT	LIBER 1465 PAGE 1295
		Act 74, Mich. P.A. 19	
For corners in JACKSON & SURVEY & Lo	cated In: Corr	ner Code ##	STATE OF HICHIGAN
344V 1 77 1995	R R		JACKSON COUNTY RECORDED
2. ProceMontrolling S1	RR		2 MAY 95 8:22 A.M. GERALD J. McDEVITT
3. Miscellaneous S T	R R R R	R	REGISTER OF DEEDS egister of Deeds Stamp & File Number
4. Lot No, Recorded Plat			
5. Private Claims, Recorded Plat			A B C D E F G H I J K L
			2 6 5 4 3 2
RONALD L. ENGER I, in a field su	NOVEMBER 7	19	4 7 8 9 10 11 12
do hereby certify that under requirements of P in lines 1 and 2 above were in conformance current manual of survey instructions of the t	A. 74, Michigan P.A. of 1970, the with regulations and rules the	corner points mentioned erefore as required in the	6 18 17 16 15 14 13
Management or by a decree of a Court of Law a above were in conformance with the rules of t	and/or that the corner points me he Michigan Board of Land Sun	intioned in lines 3, 4 and 5	8 -19 -20 -21 -22 -23 -24
Court of Law; established, re-established, expressed below:	monumented, re-monumente	d, recovered, found as	9 10 30 29 28 27 26 25
NOTE: Not more than 4 corners, all in on this certificate.	the same town and range, (may be recorded	11 12 31 32 33 34 35 36
A. Description of original monument and 1. POST SET IN ORIGINAL GO DATE FROM FEB. 2 TO FEB. B.O. 18 N27W 64 (42.4') DO. 20 S43½E 112 (73.9' 2. ON OCTOBER 14, 1885, JOH STUMP STANDING AND REMAI	OVERNMENT SURVEY 12, WITH THE FOLL (1875) IN HOLCROFT REPOR INS OF 2ND WITNESS	BY LUCIUS LYON DWING WITNESSES TED: "CORNER GO	
W. OAK 10 N58}E 393 (2	WITH THE OLD WITH	ESSES."	\$ 2.00 REHONUHENTATION
DBL. W. OAK 8 & 7 N23W CONTINUED ON BACK B. Description of corner evidence found	f and/or method applied in	restoring or reestablishin	\$ 9.00 CORNER REHONUMENTATION
SEARCHED AT APPARENT LOC CENTERLINE OF AN ABANDON HOLE 2' DEEP INTO NATURAL DID FIND BROKEN BRICK MIX CUT SECTION OF OLD ROAD I CONSTRUCTION. BELIEVE THE HOLCROFT BENEATH THE FIR	CATION OF CORNER A ED ROAD ON A FENC GROUND AND DID A ED WITH LIMESTONE BED AND FIRE CLAY BRICK AND LIMEST ECLAY POST. ACCE POSITION AS REMON	AND FOUND ½" PINCE LINE EAST-WES NOT FIND FIRECLA BENEATH THE PI WAS PROBABLY F ONE MIX IS THE PTED THE PINCHE	CHPIPE 4' WEST OF T. EXCAVATED 6' BY 10' Y SET BY HOLCROFT BUT NCHPIPE. CORNER IS IN 6' EMOVED DURING ROAD MEMORIAL LEFT BY D PIPE AS A MARKER
C. Description of monument for corner a I-10 T1S R2W			
4 INCH DIAMETER CONCRETE 40° NAZ 31" OAK 60° NAZ CENTERLINE M-50	54.74	UMINUM CAP LS : 20 PENNY NAIL	
199° NAZ 10" HICKORY 255° NAZ 8" HICKORY	27.00	40 PENNY SPIKE	
320' NAZ 10" HICKORY	16.29 16.95	40 PENNY SPIKE 40 PENNY SPIKE	IN E SIDE * ENGER
NOTE: NAZ IS MAGNETIC AZIM	UTH MEASURED FRO	M NORTH	LAND SURVEYOR NO. 28409
Signed by Rela E	6		AND SURVEY
original by	- -	DateNO	LEMBER 7 1004

NOVEMBER 7, 1994

I-10 TIS R2W PART A CONTINUED

3. JACKSON COUNTY ROAD COMMISSION WITNESSES DATED 1921

HICKORY 12" S 45° 00'E 19.9'
W OAK 10" N 58° 15'E 26.07'
R OAK 6" S 85° 00'W 38.6'

4. RONNIE M. LESTER, LS #18998, RECORDED CORNER IN LIBER 4 OF CORNERS, PAGE 59 IN JANUARY, 1988 AS A FOUND 1" PINCH PIPE ON FENCE LINE EAST AND WEST:

FOUND NAIL ON EAST SIDE 10" OAK, NW, 17.0' FOUND NAIL ON NORTH SIDE 8" OAK, WSW, 16.8' FOUND NAIL ON WEST SIDE 20" OAK, ESE, 54.6' FOUND NAIL ON EAST SIDE 10" OAK, SSW, 27.1'

5. ALAN L. SCHEPPELMAN, LS #35998, RECORDED CORNER IN LIBER 4 OF CORNERS, PAGE 4 ON MAY, 1994, 3/4" PINCHED PIPE IN LINE WITH EAST-WEST FENCE

19 had believe the stands of

NAIL ON E SIDE 10" OAK, N40°W, 16.79"
NAIL ON N SIDE 8" OAK, S80°W, 16.24'
NAIL ON W SIDE 20" OAK, S60°E, 54.71'
NAIL ON E SIDE 10" OAK, S10°W, 27.04'