

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF--	LOCATED IN--	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY <u>8</u> T. <u>2</u> S., R. <u>2</u> E.		<u>C-4, C-5</u>
2. PROPERTY CONTROLLING IN SECTION _____, T. _____, S., R. _____ E.		
3. MISCELLANEOUS PROPERTY IN SECTION _____, T. _____, S., R. _____ E.		
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Donald L. Bissell, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on August, 1983, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

<p>C-4 $W\frac{1}{2}$ Cor. Found nothing Set 4" x 36" Conc. Mon. at mid point on line between NW corner & SW corner as called for in previous survey.</p>	<p>C-5 SW Cor. $1\frac{1}{2}$" Gas pipe in 1969 Witnesses from Jackson Cr. Rd. Comm. 6" Elm - S47°E - 32.67' 8" Elm - N35°E - 38.79' 14" Hickory - N71°W - 28.86' From M.S.H.D. 1956</p>
--	---

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

<p>C-4 4" x 36" Conc. Mon. w/aluminum cap. N35°E - 6.35' - 8" Hickory S49°E -24.20' -12" Hickory S49°W -29.83' - 4" Hickory N53°W -12.40' - 4" Hickory East - 35' ± - old N-S fence.</p>	<p>C-5 $1\frac{1}{2}$" Gas pipe in Mon. Box S47°E - 32.67' - 6" Elm N35°E - 38.79' - 8" Elm N71°W - 28.86' - 14" Hickory</p>
--	---


SIGNED BY _____ DATE _____

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____

APPROVED AND SIGNED BY Donald L. Bissell DATE _____
CHIEF OF SURVEY PARTY
MICHIGAN REGISTERED LAND SURVEYOR



SURVEYOR'S MICHIGAN REGISTRATION NO. 18655